

318*TQ Flexible Mains & Control Cable - EPR, CSP - 0.75mm² to 2.5mm²



Description

Our range of flexible TQ cables is designed for fixed wiring installations. It is a range of unarmoured cable designed to prevent the risk of electric shock in the event of fault or surge. Our TQ cable is suitable as a flexible marine cable, both on and offshore. This range of 300/500V (refer to core size in Characteristics) is heat and oil resistant, and flame retardant (HOFR).

Datasheet must be used in conjunction with 18th edition IET wiring regulations.

Key Features

Core Colours

2 core -	Blue	Brown			
3 core -	Blue	Brown	Green Yellow		
4 core -	Brown	Black	Grey	Green Yellow	
5 core -	Blue	Brown	Black	Grey	Green Yellow
6 core and above -	Black	with	White	numbers plus	Green Yellow

Standards

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

318*TQ Flexible Mains & Control Cable - EPR, CSP - 0.75mm² to 2.5mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Size
3182TQ/75	0.75	2	24/0.20	5.7	58	7.4
3183TQ/75WH	0.75	3	24/0.20	6.2	72	8.1
3184TQ/75WH	0.75	4	24/0.20	6.2	72	8.1
3182TQ1	1	2	32/0.20	6.1	80	8
3183TQ1	1	3	32/0.20	6.5	90	8.5
3184TQ1	1	4	32/0.20	7.1	110	9.3
3181TQ1/5	1.5	1	30/0.25	5.7	38	7.1
3182TQ1/5	1.5	2	30/0.25	7.6	115	7.6
3183TQ1/5	1.5	3	30/0.25	8	135	10.4
3184TQ1/5	1.5	4	30/0.25	9	170	11.6
3185TQ1/5	1.5	5	30/0.25	11.2	200	14.4
3186TQ1/5	1.5	6	30/0.25	13.4	335	17.2
3187TQ1/5	1.5	7	30/0.25	14.6	366	18.2
3180/12TQ1/5	1.5	12	30/0.25	17.6	410	22.4
3180/18TQ1/5	1.5	18	30/0.25	19.8	570	24.3
3180/19TQ1/5	1.5	19	30/0.25	21.4	710	26.7
3180/27TQ1/5	1.5	27	30/0.25	25.3	920	25.3
3181TQ2/5	2.5	1	50/0.25	6.3	41	7.9
3182TQ2/5	2.5	2	50/0.25	9	160	11.6
3183TQ2/5	2.5	3	50/0.25	9.6	195	12.4
3184TQ2/5	2.5	4	50/0.25	10.7	245	13.8
3185TQ2/5	2.5	5	50/0.25	13.3	300	17
3187TQ2/5	2.5	7	50/0.25	17.2	424	21
3180/12TQ2/5	2.5	12	50/0.25	20.6	600	26.2
3180/16TQ2/5	2.5	16	50/0.25	23.8	780	28.4
3180/20TQ2/5	2.5	20	50/0.25	26.4	1050	31.2
3180/27TQ2/5	2.5	27	50/0.25	30.1	1390	35.4
3180/37TQ2/5	2.5	37	50/0.25	35	1720	40.9

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

