

6181B Mains Cable - BS8573, XLPE, LSZH - 50mm² to 1000mm²



Description

6181B is a low smoke halogen single core cable, double insulated with a voltage rating of 600/100V. General surface wire cable for fixed installation, domestic and light industrial use. Available in Blue and Brown core, with a black sheath. Comes in sizes 500mm² - 1000mm². As this cable is used internally, it is covered by current CPR regulations.

Key Features



Voltage Rating 600/1000 Volts



Minimum Bending Radius 12 x Overall Diameter



Flame Retardancy BS EN/IEC 60332-1



Temperature Limits Temperature Range: 0°C to +90°C

Core Colours

All sizes available in Brown





Standards

- BS8573 / IEC 60502-1
- IEC 61034-1
- IEC/EN 60754-1/2
- BS EN/IEC 60332-1
- BS EN/IEC 60228

Construction

- Conductor: Class 2 stranded copper conductor
- Insulation: Cross Linked polyethylene (XLPE)
- Outer Sheath: Low Smoke Zero Halogen (LSZH)
- Sheath Colour: Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while $reducing\ carbon\ emissions\ in\ collaboration\ with\ our\ customers\ and\ suppliers.$



Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis



















$6181B\ Mains\ Cable\ -\ BS8573, XLPE, LSZH\ -\ 50mm^2\ to\ 1000mm^2\ -\ Dimensions$

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
6181B50	50	1	19/1.78	13	525	0.6	25
6181B70	70	1	19/2.14	15.5	730	0.7	25
6181B95	95	1	19/2.52	18	990	0.7	25
6181B120	120	1	37/2.03	19.5	1230	0.8	32
6181B150	150	1	37/2.25	21.5	1525	0.9	32
6181B185	185	1	37/2.52	24	1885	1	32
6181B240	240	1	61/2.25	27	2440	1.1	40
6181B300	300	1	61/2.52	29.5	3045	1.2	40
6181B400	400	1	61/2.52	33	3855	1.4	50S
6181B500	500	1	61/3.20	37.5	4950	1.6	50S
6181B630	630	1	127/2.52	42	6345	1.8	50
6181B800	800	1	127/2.85	47.5	8140	2	63S
6181B1000	1000	1	127/2.85	53	9860	TC9	63



















CENELEC

CURRENT-CARRYING CAPACITY (amperes)

Ambient temperature: 30°C

Conductor cross sectional area	Reference Method A (enclosed in conduit in thermally insulating wall etc.)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method F (in free air or on a perforated cable tray etc horizontal or vertical etc) Touching			Reference Method G (in free air) Spaced by one cable diameter	
	2 cables single phase AC or DC	3 or 4 cables, three- phase AC	2 cables single phase AC or DC	3 or 4 cables, three phase AC	2 cables single phase AC or DC flat and touching	3 or 4 cables, three phase AC flat and touching or trefoil	2 cables single phase AC or DC flat	3 cables, three phase AC flat	3 cables, three phase AC trefoil	2 cables, single-phase AC or DC or 3 cables three-phase AC flat	
										Horizontal	Vertical
mm ²	A	А	Α	Α	Α	Α	Α	Α	Α	А	А
1	14	13	17	15	19	17.5	-	-	-	-	-
1.5	19	17	23	20	25	23	-	-	-	-	-
4	35	31	42	37	46	41	-				-
6	45	40	54	48	59	54	-	-	-	-	-
10	61	54	75	66	81	74	-	-	-	-	-
16	81	73	100	88	109	99	-		-	-	
25	106	95	133	117	143	130	161	141	135	182	161
35	131	117	164	144	176	161	200	176	169	226	201
50	158	141	198	175	228	209	242	216	207	275	246
70	200	179	253	222	293	268	310	279	268	353	318
95	241	216	306	269	355	326	377	342	328	430	389
120	278	249	354	312	413	379	437	400	383	500	454
150	318	285	393	342	476	436	504	464	444	577	527
185	362	324	449	384	545	500	575	533	510	661	605
240	424	380	528	450	644	590	679	634	607	781	719
300	486	435	603	514	743	681	783	736	703	902	833
400	-	-	683	584	868	793	940	868	823	1085	1008
500	-	-	783	666	990	904	1083	998	946	1253	1169
630	-	-	900	764	1130	1033	1254	1151	1088	1454	1362
800	-	-	-	-	1288	1179	1358	1275	1214	1581	1485
1000	-	-	-		1443	1323	1520	1436	1349	1775	1671

Where it is intended to connect the cables in this table to equipment or accessories designed to operate at a temperature lower than the maximum operating temperature of the cable, the cables should be rated at the maximum operating temperature of the equipment or accessory (see Regulation 512.1.5). Where it is intended to group a cable in this table with other cables, the cables should be rated at the lowest of the maximum operating temperatures of any of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and without present of the cables of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and without present of the cables of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and the cables of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and the cables of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying carrowly and the carrowly and the

















CENELEC



0.063

0.150

0.165

TABLE 4E1B

VOLTAGE DROP (per ampere per metre)

Conductor operating temperature:90°C 2 cables, single-phase AC 3 or 4 cables, three-phase AC cables, DC Reference Methods A & R Reference Methods A & B (enclosed in conduit or trunk (enclosed in conduit or trun Cables touching Cables spaced* Cables touching, Trefoil Cables touching, Flat Cables spaced* Flat (mm2) nV/ Alm) (mV/A/m) (mV/A/m) (mV/A/m) (mV/A/m) (mV/A/m) (mV/A/m) (mV/A/m) 46 46 46 46 40 40 40 40 27 1.5 31 31 31 31 27 27 27 19 16 2.5 19 19 19 16 16 16 12 12 12 12 10 10 10 10 7.9 6.8 7.9 7.9 6.8 6.8 6.8 7.9 4.7 10 16 2.9 Х Х Х Х Х Х Х 25 1.850 1.850 0.310 1.900 1.850 0.190 1.850 1.850 0.280 1.850 1.600 0.270 1.650 1.600 0.165 1.600 1.600 0.190 1.600 1.600 0.270 1.650 35 50 0.990 1.000 0.290 1.050 0.990 0.180 1.000 0.990 0.270 1.000 0.870 0.900 0.155 0.870 0.860 0.870 70 95 0.490 0.270 0.490 0.170 0.520 0.490 0.560 0.440 0.500 0.430 0.450 0.430 0.430 0.490 120 0.390 0.410 0.260 0.480 0.390 0.165 0.430 0.390 0.250 0.470 0.350 0.230 0.420 0.340 0.140 0.370 0.340 0.165 0.380 0.340 0.240 0.420 150 0.320 0.330 0.260 0.430 0.320 0.165 0.360 0.320 0.250 0.410 0.290 0.230 0.370 0.280 0.140 0.310 0.280 0.165 0.320 0.280 0.240 0.370 185 0.250 0.270 0.260 0.370 0.260 0.165 0.300 0.250 0.250 0.360 0.230 0.230 0.320 0.220 0.140 0.260 0.220 0.165 0.280 0.220 0.240 0.330 240 0.190 0.210 0.260 0.330 0.200 0.160 0.250 0.195 0.250 0.310 0.185 0.290 0.170 0.140 0.220 0.170 0.165 0.240 0.170 0.240 0.290 300 0.155 0.175 0.250 0.310 0.160 0.160 0.220 0.155 0.250 0.290 0.150 0.220 0.270 0.140 0.140 0.195 0.135 0.160 0.210 0.135 0.240 0.270 400 0.120 0.140 0.250 0.290 0.130 0.155 0.200 0.125 0.240 0.270 0.125 0.220 0.250 0.110 0.135 0.175 0.110 0.160 0.195 0.110 0.240 0.260 500 0.093 0.120 0.250 0.280 0.105 0.155 0.185 0.098 0.240 0.260 0.100 0.220 0.240 0.090 0.135 0.160 0.088 0.160 0.180 0.085 0.240 0.250 630 0.072 0.100 0.250 0.270 0.086 0.155 0.175 0.078 0.240 0.250 0.088 0.210 0.230 0.074 0.135 0.150 0.071 0.160 0.170 0.068 0.230 0.240 0.072 800 0.056 0.150 0.170 0.064 0.240 0.250 0.062 0.130 0.059 0.165 0.055 0.230 0.240 0.145 0.155

0.045

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

0.055

0.130

0.140

0.050 0.155 0.165

0.047

0.054 0.240 0.240

















CENELEC

