

F2 Fire Resistant Mains Cable 1kV - BS7846, BS6387, MGT, XLPE, SWA,LSZH - 25mm² to 400mm²



Description

Armoured fire resistant cable, suitable for fixed installations such as power circuits, fire alarm system and emergency.

Key Features



Voltage Rating
600/1000 Volts



Flame Retardancy
BS EN 60332-3-24

Core Colours

2 core - Brown Blue

3 core - Brown Black Grey

4 core - Brown Black Grey Blue

5 core - Brown Black Grey Blue Green Yellow

Standards

Construction

- **Conductor:** Plain Annealed Stranded Copper Conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Bedding:** LSZH (Low smoke Zero Halogen)
- **Separator:** MICA/Glass Fire Barrier Tape
- **Armour:** Galvanised Steel Wire Armour (SWA)
- **Sheath:** Low smoke Zero Halogen (LSZH) to BS 7655
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance.

ecovadis

F2 Fire Resistant Mains Cable 1kV - BS7846, BS6387, MGT, XLPE, SWA,LSZH - 25mm² to 400mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Helios	Gland Size	Solace	Thermis
FP2X25	25	2	7/2.14	21.4	1100	FPC1923	25	1BC1923HT	NONE
FP3X25	25	3	7/2.14	26.6	1800	FPC2327	32	1BC2327HT	NONE
FP4X25	25	4	7/2.14	28.8	2150	FPC2732	32	1BC2732HT	NONE
FP5X25	25	5	7/2.14	32	2700	FPC2732	32	1BC2732HT	NONE
FP2X35	35	2	7/2.52	24.3	1550	FPC2327	25	1BC2327HT	NONE
FP3X35	35	3	7/2.52	29.1	2200	FPC2732	32	1BC2732HT	NONE
FP4X35	35	4	7/2.52	31.6	2650	FPC2732	32	1BC2732HT	NONE
FP5X35	35	5	NONE	NONE	NONE	NONE	NONE	1BC6571HT	2BC070083HT
FP4X50	50	4	19/1.78	33.2	3100	FPC3238	40	1BC3238HT	NONE
FP4X70	70	4	19/2.14	38.9	4400	FPC3846	40	1BC3845HT	2BC038048HT
FP2X120	120	2	37/2.03	37.1	3900	FPC3238	40	1BC3238HT	NONE
FP2X150	150	2	37/2.25	40.3	4650	FPC3846	50S	1BC3845HT	2BC038048HT
FP2X185	185	2	37/2.52	45.7	5950	FPC3846	50	1BC4551HT	2BC038048HT
FP2X240	240	2	61/2.25	50	7350	FPC4651	50	1BC4551HT	2BC048058HT
FP2X300	300	2	61/2.52	54.5	8700	FPC5157	63S	1BC5158HT	2BC048058HT



TABLE 4E2A

CURRENT-CARRYING CAPACITY (amperes)								
Conductor cross sectional area	Reference Method A (enclosed in conduit in thermally insulating wall etc.)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method E (free air or on a perforated cable tray etc, horizontal or vertical)	
	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three-phase AC	1 two-core cable*, single- phase AC or DC	1 three- or four-core cable*, three-phase AC	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three- phase AC	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three- phase AC
	(mm ²)	(A)	(A)	(A)	(A)	(A)	(A)	(A)
1	14.5	13	17	15	19	17	21	18
1.5	18.5	16.5	22	19.5	24	22	26	23
2.5	25	22	30	26	33	30	36	32
4	33	30	40	35	45	40	49	42
6	42	38	51	44	58	52	63	54
10	57	51	69	60	80	71	86	75
16	76	68	91	80	107	96	115	100
25	99	89	119	105	138	119	149	127
35	121	109	146	128	171	147	185	158
50	145	130	175	154	209	179	225	192
70	183	164	221	194	269	229	289	246
95	220	197	265	233	328	278	352	298
120	253	227	305	268	382	322	410	346
150	290	259	334	300	441	371	473	399
185	329	295	384	340	506	424	542	456
240	386	346	459	398	599	500	641	538
300	442	396	532	455	693	576	741	621
400	-	-	625	536	803	667	865	741

* with or without a protective conductor

- Where it is intended to connect the cables in this table to equipment or accessories designed to operate at a temperature lower than the maximum operating temperature of the cable, the cables should be rated at the maximum operating temperature of the equipment or accessory (see Regulation 512.1.5).
- Where it is intended to group a cable in this table with other cables, the cable should be rated at the lowest of the maximum operating temperatures of any of the cables in the group (see Regulation 512.1.5).
- For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying capacity and voltage drop.



TABLE 4E2B

VOLTAGE DROP (per ampere per metre)

Conductor operating temperature: 90°C

Conductor cross-sectional area	Two-core cable DC	Two-core cable, single-phase AC		Three- or four-core cable, three-phase AC		
(mm ²)	(mV/A/m)	(mV/A/m)		(mV/A/m)		
1	46		46		40	
1.5	31		31		27	
2.5	19		19		16	
4	12		12		10	
6	7.9		7.9		6.8	
10	4.7		4.7		4.0	
16	2.9		2.9		2.5	
		R	X	Z	R	X
25	1.85	1.85	0.160	1.90	0.160	0.140
35	1.35	1.35	0.151	1.35	1.15	0.135
50	0.98	0.99	0.155	1.00	0.86	0.1351
70	0.67	0.67	0.150	0.69	0.59	0.130
95	0.49	0.50	0.150	0.52	0.43	0.130
120	0.39	0.40	0.145	0.42	0.34	0.130
150	0.31	0.32	0.145	0.35	0.28	0.125
185	0.25	0.26	0.145	0.29	0.22	0.125
240	0.195	0.200	0.140	0.24	0.175	0.125
300	0.155	0.160	0.140	0.21	0.140	0.120
400	0.120	0.130	0.140	0.115	0.115	0.120
						0.165

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

