

# ENATS 09-6 Telecommunications Cable - SWA - 0.28mm



## Description

ENATS 09-6 Telecommunication cable is a PVC insulated, multipair, light current control cable which is intended to be used for feeder protection in control, alarm equipment and switchgear. The cable can also be used in power stations where the voltage does not exceed 150V d.c or 110V a.c. The cable can be installed where there is risk of mechanical impact due to the steel wired armouring.

## **Key Features**



Minimum Bending Radius 10 x Overall Diameter



Flame Retardancy BS EN/IEC 60332-1



Temperature Limits Fixed: -30°C to +70°C Flexing: -5°C to +70°C

## **Core Colours**

ENATS09-06 Section 3 Core ID chart

## **Standards**

- IEC/EN 60332-1-2
- IEC 332 PT1
- ENATS 09-6 Issue 8 Section 5 3.6

## Construction

- Conductor: Solid tinned annealed copper conductors twisted to form pairs
- Insulation: Polyvinyl Chloride (PVC)
- Bedding: Polyvinyl Chloride (PVC)
- Armour: Galvanised Steel Wire Armour (GSWA)
- Outer Sheath: Polyvinyl Chloride (PVC)
- Sheath Colour: Black

## **QA Lab**

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



## **Our Sustainability Commitment**

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



## ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

## ecovadis

















# ENATS 09-6 Telecommunications Cable - SWA - 0.28mm - Dimensions

Reference	Conductor Size (mm2)	No Of Pairs	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
13050	0.28	2	1/0.6	9	170	0.5	20/16
13051	0.28	5	1/0.6	12.07	238	0.6	20\$
13052	0.28	10	1/0.6	15.91	454	0.7	20
13053	0.28	20	1/0.6	17.18	496	0.7	20
13054	0.28	30	1/0.6	18.1	697	0.8	20
13055	0.28	50	1/0.6	26.6	1243	1.1	32
13056	0.28	100	1/0.6	29.8	1825	1.2	32

















CENELEC



## **ENATS 3.6 - CORE COLOURS**

PAIR NUMBER	WIRE A	WIRE B
1	BLACK	BLUE
2	BLACK	ORANGE
3	BLACK	GREEN
4	BLACK	BROWN
5	BLACK	GREY
6	BLUE	WHITE
7	BLUE	ORANGE
8	BLUE	GREEN
9	BLUE	BROWN
10	BLUE	GREY
11	ORANGE	WHITE
12	ORANGE	GREEN
13	ORANGE	BROWN
14	ORANGE	GREY
15	GREEN	WHITE
16	GREEN	BROWN
17	GREEN	GREY
18	BROWN	WHITE
19	BROWN	GREY
20	GREY	WHITE
21	BLACK	WHITE
22	BLACK	RED
23	BLACK	YELLOW
24	BLACK	VIOLET
25	WHITE	RED

PAIR NUMBER	WIRE A	WIRE B		
26	WHITE	YELLOW		
27	WHITE	VIOLET		
28	BLUE	RED		
29	BLUE	YELLOW		
30	BLUE	VIOLET		
31	GREEN	RED		
32	GREEN	YELLOW		
33	GREEN	VIOLET		
34	RED	GREY		
35	RED	ORANGE		
36	RED	YELLOW		
37	RED	BROWN		
38	RED	VIOLET		
39	GREY	YELLOW		
40	GREY	VIOLET		
41	ORANGE	YELLOW		
42	ORANGE	VIOLET		
43	YELLOW	BROWN		
44	YELLOW	VIOLET		
45	BROWN	VIOLET		
46	TURQUOISE	BLACK		
47	TURQUOISE	BLUE		
48	TURQUOISE	RED		
49	TURQUOISE	ORANGE		
50 TURQUOISE		YELLOW		

All two pair cables are in quad formation and colourcoded in rotation - Blue, Orange, Green, Brown.

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

