

NYYJ Mains & Control Cable Non-Armoured, PVC - 1.5mm² to 16mm²



Description

Unarmoured power and control cable is most suited for energy supply in fixed installations. NYY Cable can be installed indoors where there is little chance of mechanical damage. Cables can be fixed on cable trays, within conduits or fixed to walls. This cable is not suitable for direct burial.

Key Features



Voltage Rating 600/1000 Volts



Minimum Bending Radius 12 x Overall Diameter



Flame Retardancy BS EN 60332-1-2



Temperature Limits Fixed: -15°C to +70°C

Core Colours



Standards

- Generally to VDE 0276-603
- BS EN/IEC 60228
- BS EN/IEC 60332-1-2
- IEC 60502-1

Construction

- Conductor: Up to 6mm² Class 1 solid copper conductor Above 10mm² Class 2 stranded copper
- Insulation: PVC (Poly Vinyl Chloride)
- Filler: PVC (Poly Vinyl Chloride)
- Sheath: PVC (Polyvinyl Chloride)

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis





















NYYJ Mains & Control Cable Non-Armoured, PVC - 1.5mm² to 16mm² - Dimensions

| Reference | Conductor Size (mm2) | No Of Cores | Stranding(mm) | Overall Diameter(mm) | Weight(Kg/Km) | Nylon Cleat Size | Gland Size |
|-----------|----------------------|-------------|---------------|-------------------------|---------------|------------------|------------|
| NYY2X1/5 | 1.5 | 2 | 1/1.38 | 10.5 | 157 | 0.5 | 20S |
| NYY3X1/5 | 1.5 | 3 | 1/1.38 | 11 | 190 | 0.5 | 20 |
| NYY4X1/5 | 1.5 | 4 | 1/1.38 | 11.8 | 220 | 0.5 | 20 |
| NYY5X1/5 | 1.5 | 5 | 1/1.38 | 12.8 | 270 | 0.6 | 20 |
| NYY7X1/5 | 1.5 | 7 | 1/1.38 | 13.7 | 299 | 0.6 | 25 |
| NYY2X2/5 | 2.5 | 2 | 1/1.78 | 11.3 | 193 | 0.5 | 20 |
| NYY3X2/5 | 2.5 | 3 | 1/1.78 | 11.9 | 240 | 0.5 | 20 |
| NYY4X2/5 | 2.5 | 4 | 1/1.78 | 12.8 | 290 | 0.6 | 20 |
| NYY5X2/5 | 2.5 | 5 | 1/1.78 | 13.9 | 350 | 0.6 | 25 |
| NYY7X2/5 | 2.5 | 7 | 1/1.78 | 14.9 | 388 | 0.6 | 25 |
| NYY2X4 | 4 | 2 | 1/2.25 | 13 | 267 | 0.6 | 20 |
| NYY3X4 | 4 | 3 | 1/2.25 | 13.7 | 330 | 0.6 | 25 |
| NYY4X4 | 4 | 4 | 1/2.25 | 14.8 | 400 | 0.6 | 25 |
| NYY5X4 | 4 | 5 | 1/2.25 | 16.3 | 480 | 0.7 | 25 |
| NYY2X6 | 6 | 2 | 1/2.76 | 14 | 329 | 0.6 | 25 |
| NYY3X6 | 6 | 3 | 1/2.76 | 14.8 | 420 | 0.6 | 25 |
| NYY4X6 | 6 | 4 | 1/2.76 | 16 | 510 | 0.7 | 25 |
| NYY5X6 | 6 | 5 | 1/2.76 | 17.6 | 600 | 0.7 | 25 |
| NYY2X10 | 10 | 2 | 7/1.35 | 16.6 | 498 | 0.7 | 25 |
| NYY3X10 | 10 | 3 | 7/1.35 | 17.8 | 580 0.8 | | 25 |
| NYY4X10 | 10 | 4 | 7/1.35 | 19.3 | 751 0.8 | | 32 |
| NYY5X10 | 10 | 5 | 7/1.35 | 21.2 910 0.9 | | 0.9 | 32 |
| NYY2X16 | 16 | 2 | 7/1.70 | 18.8 | 18.8 684 0.8 | | 25 |
| NYY3X16 | 16 | 3 | 7/1.70 | 20.2 | 20.2 800 0.9 | | 32 |
| NYY4X16 | 16 | 4 | 7/1.70 | 22 | 22 1057 0.9 | | 32 |
| NYY5X16 | 16 | 5 | 7/1.70 | 24.2 | 1257 | 1 | 32 |



















GENERAL CONDUCTOR PROPERTIES

| NOMINAL CROSS SECTION AREA MM2 | MAX RESISTANCE (Q/Km) OF CLASS 1 SOLID CONDUCTOR AT 20 0C | MINIMUM NUMBER OF WIRES IN CLASS 2 CONDUCTOR | | | | | DUCTOR | MAX RESISTANCE (Ω/Km) OF CLASS 2 COPPER CONDUCTOR AT 20 0C | MAX RESISTANCE(Q/Km) OF CLASS 2 ALUMINIUM CONDUCTOR AT 20 0C |
|--------------------------------------|---|--|----|-----------------------|----|---------------|--------|--|--|
| | | CIRCULAR | | COMPACTED CIRCULAR | | SECTOR SHAPED | | CONDUCTOR AT 20 0C | CONDUCTOR AT 20 0C |
| | | Cu | Al | Cu | Al | Cu | Al | | |
| 1.5 | 12.1 | 7 | | 6 | | | | 12.1 | - |
| 2.5 | 7.41 | 7 | - | 6 | - | - | - | 7.41 | - |
| 4 | 4.61 | 7 | - | 6 | - | - | - | 4.61 | - |
| 6 | 3.08 | 7 | - | 6 | - | - | - | 3.08 | - (a) (a) (a) (b) (b) (b) (b) |
| 10 | 1.83 | 7 | 7 | 6 | 6 | - | - | 1.83 | 3.08 |
| 16 | 1.15 | 7 | 7 | 6 | 6 | - | - | 1.15 | 1.91 |
| 25 | 0.727 | 7 | 7 | 6 | 6 | 6 | 6 | 0.727 | 1.2 |
| 35 | 0.524 | 7 | 7 | 6 | 6 | 6 | 6 | 0.524 | 0.868 |
| 50 | 0.387 | 19 | 19 | 6 | 6 | 6 | 6 | 0.387 | 0.641 |
| 70 | 0.268 | 19 | 19 | 12 | 12 | 12 | 12 | 0.268 | 0.443 |
| 95 | 0.193 | 19 | 19 | 15 | 15 | 15 | 15 | 0.193 | 0.32 |
| 120 | 0.153 | 37 | 37 | 18 | 15 | 18 | 15 | 0.153 | 0.253 |
| 150 | 0.124 | 37 | 37 | 18 | 15 | 18 | 15 | 0.124 | 0.206 |
| 185 | 0.101 | 37 | 37 | 30 | 30 | 30 | 30 | 0.0991 | 0.164 |
| 240 | 0.0775 | 37 | 37 | 34 | 30 | 34 | 30 | 0.0754 | 0.125 |
| 300 | 0.062 | 61 | 61 | 34 | 30 | 34 | 30 | 0.0601 | 0.1 |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

