

Tata Type143 BSC Cable - 0.75mm²



Description

TATA 143 cable is used for transmitting digital and analogue communication signals in instrumentation and control systems. The cable can be used in Group II classified areas of zones 1 and 2 (IEC 60079-14).

Key Features



Voltage Rating
300/500 Volts



Minimum Bending Radius
12 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1



Temperature Limits
Temperature Range: -20°C to +70°C

Core Colours

ENATS09-06 Section 3 Core ID Chart

Standards

- TATA TYPE 143
- BS EN/IEC 60332-1
- BS EN/IEC 60228
- BS EN 50363-4-1

Construction

- **Conductor:** Class 5 Flexible Tinned Copper
- **Insulation:** Polyvinyl Chloride (PVC)
- **Screen:** Collective Aluminium/mylar tape with 0.5mm drain wire
- **Overall Tape Screen:** Polyester tape wrapping
- **Bedding:** Polyvinyl Chloride (PVC)
- **Armour:** Steel Wire Armour (SWA)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Orange

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Tata Type143 BSC Cable - 0.75mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Pairs	Stranding(mm)	Outside Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
BSC1431P	0.75	1	24/0.20	10.7	260	0.5	20/16
BSC1432P	0.75	2	24/0.20	11.9	320	0.5	20S
BSC1435P	0.75	5	24/0.20	18.8	672	0.8	20
BSC14310P	0.75	10	24/0.20	24.3	1112	1.0	25
BSC14320P	0.75	20	24/0.20	30.3	1665	1.2	32
BSC14330P	0.75	30	24/0.20	36.5	2525	1.6	40
BSC14350P	0.75	50	24/0.20	46.0	4137	2.0	50

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

