

ARE4H5EX - Compact Cable 12/20KV



Description

Medium Voltage triplex form screened power cable for wind generation facilities. Polyethylene outer sheath makes it suitable for laying in underground channels or pipe and laying in open air. Can be buried underground as long as it is installed with adequate protection.

Key Features



Voltage Rating
12/20 (24)kV



Minimum Bending Radius
20x Overall Diameter



Temperature Limits
Minimum Installation Temperature: -25°C
Maximum Operating Temperature: +90°C
Maximum Short Circuit Temperature: +250°C

Standards

- HD 620
- IEC 60502-2
- IEC 60228

Construction

- **Conductor:** Class 2 Stranded Circular Compacted Aluminium Conductor
- **Conductor Screen:** Semi conductive XLPE
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi conductive XLPE
- **Water Blocking:** Semi-conductive swellable tape
- **Metallic Screen:** Aluminium tape longitudinally applied
- **Outer Sheath:** Cross-Linked Polyethylene (XLPE) Type DIX 8
- **Sheath Colour:** Red

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

ARE4H5EX - Compact Cable 12/20KV - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Nominal Conductor Diameter	Minimum Bending Radius	Overall Diameter(mm)	Weight(Kg/Km)
ARE4H5EX20KV3X50	50	3	8.5	550	27.5	1750
ARE4H5EX20KV3X70	70	3	9.8	570	28.5	1950
ARE4H5EX20KV3X95	95	3	11.5	600	30.0	2250
ARE4H5EX20KV3X120	120	3	13.0	640	32.0	2500
ARE4H5EX20KV3X150	150	3	14.5	660	33.0	2825
ARE4H5EX20KV3X185	185	3	16.0	700	35.0	3275
ARE4H5EX20KV3X240	240	3	18.5	740	37.0	3950
ARE4H5EX20KV3X300	300	3	21.0	820	41.0	4750

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

