

# Belden Equivalent 9841 SWA



## Description

Single pair plus drain cable which is equivalent to Belden 9841. Collectively foil screened cables for interference free high speed data transmission in digital communication systems.

## **Key Features**



Voltage Rating 300 Volts



**Minimum Bending Radius** 

Fixed: 10 x Overall Diameter Flexing: 15 x Overall Diameter



**Temperature Limits** 

Temperature Range: -30°C to +80°C

#### **Core Colours**

Pair 1: White

## **Standards**

- IEC 60332-1-2
- EIA RS-485
- UL1685
- ASTM D 1239

#### Construction

- Conductor: Stranded tinned copper
- Insulation: Polyethylene (PE)
- Insulation Screen: Aluminium/Polyester Tape Screen (AL/PET)
- Drain Wire: Tinned Copper
- Braiding: Tinned Copper Wire Braiding (TCWB)
- Bedding: Polyvinyl Chloride (PVC)
- Armour: Galvanised Steel Wire Armour (GSWA)
- Outer Sheath: Polyvinyl Chloride (PVC)
- . Sheath Colour: Grey

## **QA Lab**

## Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



# **Our Sustainability Commitment**

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

# ecovadis



















# Belden Equivalent 9841 SWA - Dimensions

Reference	AWG Stranding	No Of Conductors	No Of Pairs	Overall Diameter(mm)	Weight(Kg/Km)
CD9841SWA	AWG 24(7x32)	2 Plus Drain Wire	1	10.3	215

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

