

F2 Fire Resistant Mains Cable 1kV - BS7846, BS6387, MGT, XLPE, SWA, LSZH - 1.5mm² to 16mm²



Description

Fireproof Mains Cable available in sizes 1.5mm to 16mm and manufactured to British Standard BS7846 F2 / BS6387 & CWZ. The cable features plain annealed stranded copper conductor, mica fire resistant tape, thermosetting XLPE insulated, low smoke & zero halogen (LSZH) bedding, galvanised steel wire armour, low smoke & zero halogen (LSZH) outer sheath. Fire resistant to BS7846 F2 / BS6387 & CWZ. Acid gas emission to BS EN 50267 (IEC60754), smoke emission to BS EN 50268 (IEC 61034) and flame propagation to BS EN 50265, BS EN 50266 (IEC 60332-3). Suitable for fixed installations such as power circuits, fire alarm systems and emergency lighting.

Key Features



Voltage Rating
600/1000 Volts



Minimum Bending Radius
8 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1
BS EN/IEC 60332-3-24



Temperature Limits
Fixed -20°C to +90°C

Core Colours

- 2 core - Brown Blue
- 3 core - Brown Black Grey
- 4 core - Brown Black Grey Blue
- 5 core - Brown Black Grey Blue Green Yellow

** 5 cores only stocked in Coloured Cores.

Standards

- IEC 60332-3-24
- BS EN/IEC 60332-1-2
- BS EN/IEC 61034-2
- BS EN/IEC 60228
- Fire resistant to BS7846 F2
- BS EN/IEC 60754-1
- BS6387 Cat CWZ

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Bedding:** Low Smoke Zero Halogen (LSZH)
- **Fire Protection:** MICA Glass Fibre Tape
- **Armour:** Steel Wire Armour (SWA)
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

F2 Fire Resistant Mains Cable 1kV - BS7846, BS6387, MGT, XLPE, SWA, LSZH - 1.5mm² to 16mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Outside Diameter(mm)	Weight(Kg/Km)	Helios	Gland Size	Solace
6942F1/5	1.5	2	7/0.53	12	295	FPC1013	20/16	1BC1013HT
6943F1/5	1.5	3	7/0.53	12.5	324	FPC1013	20/16	1BC1013HT
6944F1/5	1.5	4	7/0.53	13.3	367	FPC1316	20S	1BC1316HT
6945F1/5CC	1.5	5	7/0.53	15.00	100	FPC1316	20S	1BC1316HT
6947F1/5	1.5	7	7/0.53	15.3	463	FPC1316	20S	1BC1316HT
6940/12F1/5	1.5	12	7/0.53	20	791	FPC1923	25	1BC1923HT
6940/19F1/5	1.5	19	7/0.53	22.9	1030	FPC1923	25	1BC1923HT
6940/27F1/5	1.5	27	7/0.53	27.9	1534	FPC2732	32	1BC2732HT
6940/37F1/5	1.5	37	7/0.53	30.7	1849	FPC2732	32	1BC2732HT
6942F2/5	2.5	2	7/0.67	13.1	352	FPC1316	20S	1BC1316HT
6943F2/5	2.5	3	7/0.67	13.7	392	FPC1316	20S	1BC1316HT
6944F2/5	2.5	4	7/0.67	14.7	454	FPC1316	20S	1BC1316HT
6945F2/5CC	2.5	5	7/0.67	15.7	530	FPC1316	20	1BC1316HT
6947F2/5	2.5	7	7/0.67	17	584	FPC1619	20	1BC1619HT
6940/12F2/5	2.5	12	7/0.67	22.5	1003	FPC1923	25	1BC1923HT
6940/19F2/5	2.5	19	7/0.67	27	1525	FPC2327	32	1BC2327HT
6940/27F2/5	2.5	27	7/0.67	31.6	1990	FPC2732	32	1BC2732HT
6940/37F2/5	2.5	37	7/0.67	34.8	2435	FPC3238	40	1BC3238HT
6942F4	4	2	7/0.85	14.1	424	FPC1316	20S	1BC1316HT
6943F4	4	3	7/0.85	14.8	478	FPC1316	20S	1BC1316HT
6944F4	4	4	7/0.85	16	556	FPC1316	20	1BC1316HT
6945F4CC	4	5	7/0.85	18.12	725	FPC1619	20	1BC1619HT
6947F4	4	7	7/0.85	19.5	852	FPC1923	20	1BC1923HT
6942F6	6	2	7/1.04	15.2	504	FPC1316	20	1BC1316HT
6943F6	6	3	7/1.04	16	573	FPC1316	20	1BC1316HT
6944F6	6	4	7/1.04	18.2	783	FPC1619	20	1BC1619HT
6945F6CC	6	5	7/1.04	19.65	865	FPC1923	20	1BC1923HT
6942F10	10	2	7/1.35	16.9	620	FPC1619	20	1BC1619HT
6943F10	10	3	7/1.35	18.5	868	FPC1619	20	1BC1619HT
6944F10	10	4	7/1.35	20	1029	FPC1923	25	1BC1923HT
6945F10	10	5	7/1.35	22.64	1222	FPC1923	25	1BC1923HT
6942F16	16	2	7/1.70	19.5	954	FPC1923	25	1BC1923HT
6943F16	16	3	7/1.70	20.8	1136	FPC1923	25	1BC1923HT
6944F16	16	4	7/1.70	22.5	1367	FPC1923	25	1BC1923HT

TABLE 4E2A

CURRENT-CARRYING CAPACITY (amperes)

Ambient temperature: 30°C
Conductor operating temperature: 90°C

Conductor cross sectional area	Reference Method A (enclosed in conduit in thermally insulating wall etc.)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method E (free air or on a perforated cable tray etc, horizontal or vertical)	
	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three-phase AC	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three-phase AC	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three-phase AC	1 two-core cable*, single-phase AC or DC	1 three- or four-core cable*, three-phase AC
(mm ²)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)
1	14.5	13	17	15	19	17	21	18
1.5	18.5	16.5	22	19.5	24	22	26	23
2.5	25	22	30	26	33	30	36	32
4	33	30	40	35	45	40	49	42
6	42	38	51	44	58	52	63	54
10	57	51	69	60	80	71	86	75
16	76	68	91	80	107	96	115	100
25	99	89	119	105	138	119	149	127
35	121	109	146	128	171	147	185	158
50	145	130	175	154	209	179	225	192
70	183	164	221	194	269	229	289	246
95	220	197	265	233	328	278	352	298
120	253	227	305	268	382	322	410	346
150	290	259	334	300	441	371	473	399
185	329	295	384	340	506	424	542	456
240	386	346	459	398	599	500	641	538
300	442	396	532	455	693	576	741	621
400	-	-	625	536	803	667	865	741

* with or without a protective conductor

1. Where it is intended to connect the cables in this table to equipment or accessories designed to operate at a temperature lower than the maximum operating temperature of the cable, the cables should be rated at the maximum operating temperature of the equipment or accessory (see Regulation 512.1.5).
2. Where it is intended to group a cable in this table with other cables, the cable should be rated at the lowest of the maximum operating temperatures of any of the cables in the group (see Regulation 512.1.5).
3. For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying capacity and voltage drop.

TABLE 4E2B

VOLTAGE DROP (per ampere per metre)

Conductor operating temperature:90°C

Conductor cross-sectional area (mm ²)	Two-core cable DC	Two-core cable, single-phase AC			Three- or four-core cable, three-phase AC		
	(mV/A/m)	(mV/A/m)			(mV/A/m)		
1	46	46			40		
1.5	31	31			27		
2.5	19	19			16		
4	12	12			10		
6	7.9	7.9			6.8		
10	4.7	4.7			4.0		
16	2.9	2.9			2.5		
		R	X	Z	R	X	Z
25	1.85	1.85	0.160	1.90	0.160	0.140	1.65
35	1.35	1.35	0.151	1.35	1.15	0.135	1.15
50	0.98	0.99	0.155	1.00	0.86	0.1351	0.87
70	0.67	0.67	0.150	0.69	0.59	0.130	0.60
95	0.49	0.50	0.150	0.52	0.43	0.130	0.45
120	0.39	0.40	0.145	0.42	0.34	0.130	0.37
150	0.31	0.32	0.145	0.35	0.28	0.125	0.30
185	0.25	0.26	0.145	0.29	0.22	0.125	0.26
240	0.195	0.200	0.140	0.24	0.175	0.125	0.21
300	0.155	0.160	0.140	0.21	0.140	0.120	0.185
400	0.120	0.130	0.140	0.115	0.115	0.120	0.165

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.