DNO Approved CNE Aluminium Straight Concentric Cable - XLPE, PVC - 25mm² to 35mm²



Description

Used by Distribution Network Operators (DNOs) such as UKPN, ENW, NPG, SSE etc to provide the final connection to domestic properties. Suitable for sub main distribution boxes, street lighting systems and high rise buildings.

CNE (Combined Negative & Earth) Construction for modern installations

Key Features



Voltage Rating 600/1000 Volts



Minimum Bending Radius 8 x Overall Diameter



Flame Retardancy BS EN 60332-1-2



Temperature Limits Temperature Range: -15°C to + 70°C

Standards

- BS7870-3-11
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228

Construction

- Conductor: Solid Aluminium Conductor
- Insulation: Cross Linked polyethylene (XLPE)
- Concentric Conductor: Single layer of copper wires
- Separator: Binding Tape Helically Applied
- Outer Sheath: Polyvinyl Chloride (PVC)
- Sheath Colour: Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while $reducing\ carbon\ emissions\ in\ collaboration\ with\ our\ customers\ and\ suppliers.$



Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis





















DNO Approved CNE Aluminium Straight Concentric Cable - XLPE, PVC - 25mm² to 35mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Overall Diameter(mm)	Weight(Kg/Km)
25STRCONAL	25	1	13	300
3X25STRCONAL	25	3	23	650
3X35STRCONAL	35	3	25	820
35STRCONAL	35	3	14	390















CENELEC



CONCENTRIC CABLE CURRENT CARRYING CAPACITY							
	NOMINAL CROSS SECTIONAL AREA	CONTINUOUS CURRENT RATING					
NUMBER OF CORES		CLIPPED DIRECT	IN CONDUIT ON WALL	IN AIR			
	(MM2)	AMPS	AMPS	AMPS			
1	25	119	105	127			
3	25	90	84	97			
1	35	147	128	158			
3	35	112	103	120			

















CENELEC



CONCENTRIC CABLE ELECTRIC CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C	MAXIMUM AC RESISTANCE OF CONDUCTOR AT 20°C -	MAXIMUM DC RESISTANCE OF CONCENTRIC CONDUCTOR AT 20°C -
(MM2)	Ω/ΚΜ	Ω/ΚΜ	Ω/ΚΜ
25	1.2	1.54	1.3
35	0.868	1.11	0.91

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

