

ConnectEV LSZH Electric Vehicle Charging & 4 Pair FTP CAT5e Cable



Description

ConnectEV, EV charging cable, LSZH, armoured EV cable, CAT5e FTP, power and data cable, double sheathed, electric vehicle charge points, halogen free

Key Features



Voltage Rating
600 - 1000 Volts
Test Voltage: 4kV



Minimum Bending Radius
6x overall diameter



Flame Retardancy
BS EN/IEC 60332-1
BS EN/IEC 60332-3-24



Temperature Limits
Temperature Range: -30°C to +80°C

Core Colours

3 Core -	Brown	Blue	Green Yellow
Pair 1 -	Blue	Blue	White
Pair 2 -	Orange	Orange	White
Pair 3 -	Green	Green	White
Pair 4 -	Brown	Brown	White

Standards

- BS EN/IEC 60332-3-24 (cat C)
- IEC 60754-1
- IEC 61034-2
- BS EN/IEC 60332-1-2
- BS EN/IEC 60502-1
- BS EN/IEC 60228
- FG16OR16

Construction

- **Conductor: Power Cable:** Class 5 Flexible Stranded Copper, **CAT5 Cable:** Class 1 Solid Copper
- **Conductor:** Class 5 Flexible stranded copper
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation: Power Cable:** XLPE, **CAT5 Cable:** PVC
- **Bedding:** Low Smoke Zero Halogen (LSZH)
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

ConnectEV LSZH Electric Vehicle Charging & 4 Pair FTP CAT5e Cable - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)
CONNECTEV3X4LSZH	4	3+Cat5e	Class 5	17.6	455
CONNECTEV3X6LSZH	6	3+Cat5e	Class 5	19.5	740

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.