

N1XE-R/U Cable 10mm² to 16mm²



Description

Swedish standard N1XE copper power cables are a low voltage power cable with a rating of 0.6/1kV primarily for use in fixed installations. They are available with black numbered cores for N1XE-U or colour-coded cores as N1XE-R.

Key Features



Voltage Rating
600/1000 Volts



Minimum Bending Radius
12 x Overall Diameter



Temperature Limits
Minimum laying temperature: -20°C
Operating temperature: -50°C to +90°C
Maximum Conductor temperature: +90°C

Core Colours

N1XE-R

4 core -	Brown	Black	Grey	Green Yellow	
5 core -	Brown	Black	Grey	Green Yellow	Black

N1XE-U

4 core -	Black	cores with	White	numbers
5 core -	Black	cores with	White	numbers

Standards

- SS 424 14 18
- BS EN/IEC 60228
- HD 603 S1

Construction

- **Conductor:** Class 1 solid copper conductor
Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Inner Sheath:** Rubber Compound
- **Outer Sheath:** UV resistant Polyethylene compound (PE)
- **Sheath Colour:** Black or Yellow

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



N1XE-R/U Cable 10mm² to 16mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Conductor Type	Overall Diameter(mm)	Weight(Kg/Km)
N1XE/R1KV4X10	10	4	SOLID	17.5	585
N1XE/U1KV4X10	10	4	SOLID	17.5	590
N1XE/R1KV5X10	10	5	SOLID	19.0	695
N1XE/U1KV5X10	10	5	SOLID	19.0	700
N1XE/R1KV4X16	16	4	STRANDED	22.0	970
N1XE/U1KV4X16	16	4	STRANDED	22.0	975
N1XE/R1KV5X16	16	5	STRANDED	24.0	1120
N1XE/U1KV5X16	16	5	STRANDED	24.0	1125

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

