

# N2XS(FL)2Y 12/20 (24)kV Cable - 50mm<sup>2</sup> to 630mm<sup>2</sup>

## Description

Medium voltage MDPE power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. N2XS(FL)2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The cable has a UV Resistant outer sheath and three water blocking layers to make it water resistant

## **Key Features**



Voltage Rating 12/20 (24kV)



Minimum Bending Radius 15 x Overall Diameter



#### **Temperature Limits**

Temperature Range: -20°C to +60°C Conductor Operating Temperature: +90°C Short Circuit Temperature up to 5 sec: 250°C

#### **Standards**

- BS EN 60332-1-2
- UV Resistant: ISO 4892-3
- IEC 60228
- IEC 60502-2
- IEC 60332-1-2

## Construction

- Conductor: Class 2 stranded copper conductor
- Conductor Screen: Semi-Conductive material
- Insulation: Cross Linked polyethylene (XLPE)
- Insulation Screen: Semi-Conductive XLPE
- Longditudinal Waterblocking: Semi-conductive swellable tape
- Screen: Copper wires and copper tape
- Metallic Screen: Copper Wires plus Copper tape
- Waterblocking Tape: Al/PET (Aluminium/Polyester) Tape bonded to sheath
- Longditudinal Water Blocking: Swellable tapes
- Outer Sheath: Medium Density Polyethylene (MDPE)
- Sheath Colour: Red or Black

### **QA Lab**

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



## Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



## ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

## ecovadis



















## N2XS(FL)2Y 12/20 (24)kV Cable - 50mm<sup>2</sup> to 630mm<sup>2</sup> - Dimensions

| Reference                | Conductor Size<br>(mm2) | Nominal Conductor<br>Diameter | Insulation<br>Thickness (mm) | CWS(mm) | Sheath Thickness<br>(mm) | Overall<br>Diameter(mm) | Weight(Kg/Km) |
|--------------------------|-------------------------|-------------------------------|------------------------------|---------|--------------------------|-------------------------|---------------|
| 12/20N2XS(FL)2Y1<br>X50  | 50                      | 8.5                           | 5.0                          | RM/16   | 1.8                      | 28.0                    | 1140          |
| 12/20N2XS(FL)2Y1<br>X70  | 70                      | 10.0                          | 5.0                          | RM/16   | 1.8                      | 29.5                    | 1350          |
| 12/20N2XS(FL)2Y1<br>X95  | 95                      | 11.5                          | 5.0                          | RM/16   | 1.9                      | 31.5                    | 1660          |
| 12/20N2XS(FL)2Y1<br>X120 | 120                     | 13.0                          | 5.0                          | RM/16   | 1.9                      | 33.0                    | 1965          |
| 12/20N2XS(FL)2Y1<br>X150 | 150                     | 15.0                          | 5.0                          | RM/25   | 2.0                      | 34.5                    | 2310          |
| 12/20N2XS(FL)2Y1<br>X185 | 185                     | 16.0                          | 5.5                          | RM/25   | 2.0                      | 36.0                    | 2845          |
| 12/20N2XS(FL)2Y1<br>X240 | 240                     | 17.0                          | 5.5                          | RM/25   | 2.1                      | 38.5                    | 3295          |
| 12/20N2XS(FL)2Y1<br>X300 | 300                     | 21.0                          | 55                           | RM/25   | 2.2                      | 41                      | 3830          |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

