

N2XSY CU XLPE PVC - 12/20 (24)kV Cable - 50mm² to 800mm²



Description

Medium voltage XLPE / PVC power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. N2XSY cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts where there is no danger of water ingress. The cable has a UV Resistant outer sheath.

Key Features



Voltage Rating
12/20 (24)kV



Minimum Bending Radius
15 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1-2



Temperature Limits
Maximum operating temp: 90°C
Initial temperature at S.C.C for screen: 80°C
Maximum temp during short circuit: 250°C

Standards

- IEC 60502-2
- IEC 60228
- BS EN 60332-1-2

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Outer Semi Conductor:** Extruded Outer Semi Conductor (Strippable Type)
- **Screen:** Copper Wires & Helical Equalising Copper Tape
- **Inner Semi Conductor:** Extruded Inner Semi Conductor (Bonded Type)
- **Sheath:** PVC (Polyvinyl Chloride)
- **Sheath Colour:** Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

N2XSY CU XLPE PVC - 12/20 (24)kV Cable - 50mm² to 800mm² - Dimensions

| Reference | Conductor Size (mm ²) | Nominal Conductor Diameter | Insulation Thickness (mm) | CWS(mm) | Sheath Thickness (mm) | Overall Diameter(mm) | Weight(Kg/Km) |
|-----------------|-----------------------------------|----------------------------|---------------------------|---------|-----------------------|----------------------|---------------|
| 12/20N2XSY1X50 | 50 | 8.5 | 5.0 | RM/16 | 1.8 | 26.4 | 1095 |
| 12/20N2XSY1X70 | 70 | 10.0 | 5.0 | RM/16 | 1.8 | 28.5 | 1340 |
| 12/20N2XSY1X95 | 95 | 11.9 | 5.0 | RM/16 | 1.9 | 29.5 | 1595 |
| 12/20N2XSY1X120 | 120 | 13.2 | 5.0 | RM/16 | 1.9 | 31.5 | 1895 |
| 12/20N2XSY1X150 | 150 | 15.0 | 5.5 | RM/25 | 2.0 | 33.3 | 2275 |
| 12/20N2XSY1X185 | 185 | 16.5 | 5.5 | RM/25 | 2.1 | 34.5 | 2625 |
| 12/20N2XSY1X200 | 240 | 19.0 | 5.5 | RM/25 | 2.2 | 37.3 | 3240 |
| 12/20N2XSY1X300 | 300 | 21.4 | 5.5 | RM/25 | 2.3 | 39.5 | 3825 |
| 12/20N2XSY1X400 | 400 | 24.0 | 6.0 | RM/35 | 2.4 | 42.5 | 4765 |
| 12/20N2XSY1X500 | 500 | 27.0 | 6.0 | RM/35 | 2.5 | 46.2 | 5795 |
| 12/20N2XSY1X630 | 630 | 30.5 | 6.0 | RM/35 | 2.6 | 51.1 | 7280 |
| 12/20N2XSY1X800 | 800 | 37.2 | 6.0 | RM/35 | 2.7 | 55.6 | 9150 |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

