

NA2X2Y Cable 0.6/1kV IEC 60502-1 AL/XLPE/MDPE - 16mm² to 1000mm²



Description

NA2X2Y are Low voltage Aluminium, XLPE insulation and MDPE / HDPE sheathed power cables for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2X2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The MDPE sheath is UV Resistant and water resistant to AD7.

Key Features



Voltage Rating
600V-1000V AC
1.8kV DC



Minimum Bending Radius
Single Core 15 x Overall Diameter
Multicore 12 x Overall Diameter



Temperature Limits
Maximum operating temperature of conductor: +90°C
Maximum short-circuit temperature up to 5 sec: +250°C

Standards

- IEC 60502-1
- IEC 60228
- IEC/EN 60754-1/2
- UV Resistant: ISO 4892-2

Construction

- **Conductor:** Class 2 Stranded Aluminium Conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Outer Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

NA2X2Y Cable 0.6/1kV IEC 60502-1 AL/XLPE/MDPE - 16mm² to 1000mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Insulation Thickness (mm)	Sheath Thickness (mm)	Max Overall Dia	Minimum Bending Radius	Weight(Kg/Km)
1KVNA2X2Y1X16	16	1	0.8	1.5	9.0	135	95
1KVNA2X2Y1X25	25	1	0.9	1.5	10.2	152	125
1KVNA2X2Y1X35	35	1	1.0	1.5	11.2	168	160
1KVNA2X2Y1X50	50	1	1.0	1.5	12.6	190	205
1KVNA2X2Y1X70	70	1	1.1	1.5	14.5	218	275
1KVNA2X2Y2X70	70	2	1.1	1.8	28.0	336	775
1KVNA2X2Y3X70	70	3	1.2	2.0	26.5	320	875
1KVNA2X2Y4X70	70	4	1.1	2.1	30.5	366	1105
1KVNA2X2Y1X95	95	1	1.2	1.5	16.5	248	360
1KVNA2X2Y2X95	95	2	1.2	2.0	32.0	384	995
1KVNA2X2Y3X95	95	3	1.2	2.2	29.5	355	1095
1KVNA2X2Y4X95	95	4	1.1	2.2	33.0	396	1410
1KVNA2X2Y1X120	120	1	1.4	1.6	17.8	268	445
1KVNA2X2Y2X120	120	2	1.4	2.2	34.5	415	1240
1KVNA2X2Y3X120	120	3	1.3	2.3	33.0	396	1400
1KVNA2X2Y4X120	120	4	1.2	2.4	37.0	444	1795
1KVNA2X2Y1X150	150	1	1.6	1.7	20.5	308	550
1KVNA2X2Y2X150	150	2	1.6	2.3	40.0	480	1575
1KVNA2X2Y3X150	150	3	1.4	2.4	36.0	432	1715
1KVNA2X2Y4X150	150	4	1.4	2.6	42.0	504	2220
1KVNA2X2Y1X185	185	1	1.7	1.7	21.8	330	665
1KVNA2X2Y2X185	185	2	1.6	2.5	43.0	516	1895
1KVNA2X2Y3X185	185	3	1.5	2.6	40.0	480	2120
1KVNA2X2Y4X185	185	4	1.5	2.7	46.5	558	2760
1KVNA2X2Y1X240	240	1	1.8	1.8	24.8	372	840
1KVNA2X2Y2X240	240	2	1.8	2.6	48.0	576	2395
1KVNA2X2Y3X240	240	3	1.6	2.8	45.0	540	2680
1KVNA2X2Y4X240	240	4	1.7	3.0	52.5	630	3500
1KVNA2X2Y1X300	300	1	2.0	1.8	27.4	411	1040
1KVNA2X2Y2X300	300	2	1.8	2.8	54.0	648	2995
1KVNA2X2Y3X300	300	3	1.8	3.0	50.0	600	3290
1KVNA2X2Y4X300	300	4	1.9	3.1	58.0	696	4325
1KVNA2X2Y1X400	400	1	2.2	1.9	31.0	465	1340
1KVNA2X2Y2X400	400	2	2.0	3.0	60.0	720	3795
1KVNA2X2Y3X400	400	3	2.0	3.2	57.0	684	4325
1KVNA2X2Y4X400	400	4	2.1	3.3	66.5	792	5695
1KVNA2X2Y1X500	500	1	2.2	2.0	34.5	518	1675

Reference	Conductor Size (mm2)	No Of Cores	InsulationThickness (mm)	Sheath Thickness (mm)	Max Overall Dia	Minimum Bending Radius	Weight(Kg/Km)
1KVNA2X2Y1X630	630	1	2.4	2.2	39.0	585	2195
1KVNA2X2Y1X800	800	1	2.7	2.2	45.0	675	2850
1KVNA2X2Y1X1000	1000	1	3.0	2.4	50.0	765	3495

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.