

NA2XS(F)2Y 6/10 (12)kV Cable - 50mm2 to 630mm2



Description

Medium voltage power cables with aluminium Conductor for distribution networks. This cable is used extensively in the renewables and datacentre sectors. NA2XS2Y cable is suitable for external installation. Cables can be fixed on cable trays, within conduits or fixed to walls and is suitable for burial in ducts. The cable has two waterblocking layers and a UV Resistant outer sheath.

Key Features



Voltage Rating 6/10 (12)kV



Minimum Bending Radius 15 x Overall Diameter



Flame Retardancy BS EN/IEC 60332-1-2



Temperature Limits

Temperature Range: -20°C to +60°C Conductor Operating Temperature: +90°C Short Circuit Temperature up to 5 sec: 250°C

Standards

- UV Resistant: ISO 4892-3
- BS EN 60332-1-2
- IEC 60228
- IEC 60502-2
- IEC 60332-1-2

Construction

- Conductor: Class 2 Stranded Aluminium Conductor
- Conductor Screen: Semi-Conductive material
- Insulation: Cross Linked polyethylene (XLPE)
- Insulation Screen: Semi-Conductive XLPE
- Longditudinal Waterblocking: Semi-conductive swellable tape
- Metallic Screen: Copper Wires plus Copper tape
- Longditudinal Water Blocking: Swellable tapes
- Outer Sheath: Medium Density Polyethylene (MDPE)
- Sheath Colour: Red or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis



















NA2XS(F)2Y 6/10 (12)kV Cable - 50mm² to 630mm² - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	Insulation Thickness (mm)	CWS(mm)	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
6/10NA2XS(F)2Y1X 50	50	8.5	3.0	RM/16	1.7	23.0	575
6/10NA2XS(F)2Y1X 70	70	10.0	3.0	RM/16	1.7	24.5	675
6/10NA2XS(F)2Y1X 95	95	11.6	3.0	RM/16	1.8	26.0	785
6/10NA2XS(F)2Y1X 120	120	13.0	3.2	RM/16	1.8	27.5	900
6/10NA2XS(F)2Y1X 150	150	14.5	3.2	RM/25	1.9	29.0	1155
6/10NA2XS(F)2Y1X 185	185	16	3.2	RM/25	1.9	31.5	1250
6/10NA2XS(F)2Y1X 240	240	18.5	3.2	RM/25	2.0	33.5	1450
6/10NA2XS(F)2Y1X 300	300	21.0	3.4	RM/25	2.2	36.5	1665
6/10NA2XS(F)2Y1X 400	400	23.5	3.4	RM/35	2.2	39.5	2075
6/10NA2XS(F)2Y1X 500	500	26.0	3.4	RM/35	2.4	42.6	2595
6/10NA2XS(F)2Y1X 630	630	30.5	3.4	RM/35	2.4	46.8	3115

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.



















CENELEC