

# (N)TMCGCWÖU14/25 (30kV) Cable - 25mm<sup>2</sup> to 630mm<sup>2</sup>



### Description

(N)TMCGCWÖU cable is Medium voltage, class 5 single core cable with added semiconductive material between each of the Core, the insulation and the earth conductor and surrounded with a rubber outer sheath. It is usually used for short-length connections of transformers and switchgear, as well as power cables on mining equipment and alongside conveyor belts.

(N)TMCGCWÖU comes in 8 different power ranges. from 3.6/6kV to 26/45kV

# **Key Features**



Voltage Rating 14/25 (30kV)



Minimum Bending Radius Fixed: 6 x overall diameter



Flame Retardancy IEC/EN 60332-1-2



**Temperature Limits** 

Fixed: -40°C to +80°C Flexing: -25°C to +80°C

Maximum Short Circuit Temperature: +250°C

# **Standards**

- Ozone resistant: BS EN/IEC 60811-403
- BS EN/IEC 60811-404
- UV Resistant: ISO 4892-2
- VDE 0295
- VDE 0250 PT812
- BS EN/IEC 60332-1-2
- IFC 60228

#### Construction

- Conductor: Class 5 tinned copper
- Conductor Screen: Semi-Conductive material
- Insulation: Quality Rubber Compound, according to VDE 0207 Part 20
- Insulation Screen: Inner and outer semi-conductive rubber layer
- Concentric Conductor: Copper wires with counter helix of copper tape
- Outer Sheath: Quality rubber compound, according to VDE 0207 part 21
- Sheath Colour: Red

### **QA Lab**

# Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







#### CPR

 ${\bf Clevel and \ Cable \ Company \ is \ committed \ to \ compliance \ with \ the \ Construction}$ Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



#### **Our Sustainability Commitment**

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

#### ecovadis





















# (N)TMCGCWÖU14/25 (30kV) Cable - 25mm<sup>2</sup> to 630mm<sup>2</sup> - Dimensions

Reference	Conductor Size (mm2)	Nominal Conductor Diameter	CWS(mm)	Max Overall Dia	Minimum Bending Radius	Weight(Kg/Km)
30KV(N)TMCGCWÖU 1X25	25	6.8	RM/16	26.5.	159	375
30KV(N)TMCGCWÖU 1X35	35	7.8	RM/16	28.0	168	1130
30KV(N)TMCGCWÖU 1X50	50	9.4	RM/16	29.5	177	1320
30KV(N)TMCGCWÖU 1X70	70	11.2	RM/16	31.5	189	1570
30KV(N)TMCGCWÖU 1X95	95	12.7	RM/16	34.0	204	1900
30KV(N)TMCGCWÖU 1X120	120	14.4	RM/16	36.0	216	2210
30KV(N)TMCGCWÖU 1X150	150	16.3	RM/25	38.5	231	2680
30KV(N)TMCGCWÖU 1X185	185	17.6	RM/25	40.5	243	3065
30KV(N)TMCGCWÖU 1X240	240	20.6	RM/25	44.0	264	3730
30KV(N)TMCGCWÖU 1X300	300	22.7	RM/25	45.0	270	4140
30KV(N)TMCGCWÖU 1X400	400	25.2	RM/35	48.0	288	5125
30KV(N)TMCGCWÖU 1X500	500	29.5	RM/35	53.5	321	6575
30KV(N)TMCGCWÖU 1X630	630	34.0	RM/35	58.0	348	83905

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.













CENELEC



