

## Railway Power Cable - Aluminium, XLPE, PVC - 16mm<sup>2</sup> to 120mm<sup>2</sup>



### Description

The rail power cables are most commonly used as the main power supply cable for signalling along the rail tracks. The aluminium conductors are generally used for primary and secondary power distribution conductors.

### Key Features



**Voltage Rating**  
600/1000 Volts



**Minimum Bending Radius**  
10 x Overall Diameter



**Temperature Limits**  
Temperature Range: -25°C to +90°C

### Core Colours

2 core



4 core



### Standards

- BR880 06/142639"
- BS EN/IEC 60228

### Construction

- **Conductor:** Class 1 Solid Aluminium
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Screen:** Aluminium / mylar foil tape screen
- **Separator:** Polyester Tape (PET)
- **Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Black

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance.



## Railway Power Cable - Aluminium, XLPE, PVC - 16mm<sup>2</sup> to 120mm<sup>2</sup> - Dimensions

Reference	Conductor Size (mm <sup>2</sup> )	No Of Cores	Overall Diameter(mm)	Weight(Kg/Km)	Rail Code	Gland Size
SAC2X16NA	16	3	14.3	420	6/142419	25
SAC2X25NA	25	3	16.6	455	6/142519	25
SAC2X35NA	35	3	18	525	6/142609	25
SAC2X50NA	50	3	20.4	620	6/142629	32
SAC2X70NA	70	2	22.8	840	6/142639	32
SAC4X70NA	70	4	30.6	1750	6/151469	40
SAC2X95NA	95	2	26.2	1020	6/142644	40
SAC4X95NA	95	4	35.5	2100	6/151494	M63
SAC4X120NA	120	4	38	2300	6/166820	M63

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

