

SSE Approved Power Cable Single Core - 11kV, XLPE, MDPE - 150mm² to 800mm²



Description

Medium voltage single core aluminium power cable designed in accordance with Scottish & Southern Electricity (SSE) requirements. Manufactured by G81-approved suppliers, this 11kV XLPE insulated, MDPE sheathed cable is intended for use in electricity distribution networks, providing reliable connections between existing grids and new sub-main developments where DNO approval is required.

Key Features



Voltage Rating
6.35kV / 11kV (12kV)



Temperature Limits
Temperature Range: 0°C to +90°C

Core Colours

Black

Standards

- BS 7870-4.10
- ES 02-0940

Construction

- **Conductor:** Solid or Stranded Aluminium Conductor
- **Conductor Screen:** Bonded semi conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi conducting compound
- **Metallic Screen:** Copper wires with equalising tape
- **Separator:** Binding Tape
- **Outer Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Red

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance.

ecovadis

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.



UK and Ireland Sales sales@clevelandcable.com | International Sales international@clevelandcable.com | UK 01642 241 133

Specification Data Sheet | Page 2 of 2



CENELEC

