


BS6622 11KV PVC SINGLE CORE COPPER SCREENED CABLE



APPLICATION

Suitable for power networks, underground, outdoors and installation in cable ducting.

Please note: the red outer sheath can be prone to fading when exposed to UV rays.

CABLE STANDARDS

BS 6622

IEC 60502

Flame propagation to BS EN60332

CONSTRUCTION

Conductor: Stranded Plain Annealed Circular Compacted Copper Conductors

Insulation: Cross Link Polyethylene (XLPE)

Metallic Screen: Individual or overall copper tape screen

Separator: Copper Tape with 10% overlap

Bedding: PVC

Armouring: Aluminium Wire Armour

Sheath: PVC outer sheath

Sheath Colour: ■ Red ■ Black

CHARACTERISTICS

Voltage Rating: 6350/11000 Volts (12KV)
Tested to Voltage and Duration of BS 6622

Temperature Limits: -15°C to 90°C

Minimum Bending Radius: As per cable manufacturer datasheet

Should not be installed at temperatures below 0°C or above +60°C

BS6622 11KV PVC SINGLE CORE COPPER SCREENED CABLE - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO. OF CORES	WEIGHT (KG/KM)	APPROX OVERALL DIAMETER (MM)			NYLON CLEAT SIZE	TREFOIL
					UNDER ARMOUR	OVER ARMOUR	OVERALL MM		
10001	50	19/1.78	1	1200	21.7	24.9	28.5	12	TASB04
10002	70	19/2.14	1	1461	23	26.2	30.0	14	TASB05
10003	95	19/2.52	1	1761	24.7	27.9	31.7	14	TASB06
10004	120	37/2.03	1	2049	26.7	29.9	33.9	14	TASB07
10005	150	37/2.25	1	2451	27.5	31.5	35.7	16	TASB08
10006	185	37/2.52	1	2848	29.3	33.3	37.5	16	TASB09
10007	240	61/2.25	1	3470	31.6	35.6	40.0	16	TASB11
10008	300	61/2.52	1	4103	34.6	38.6	43.0	18	TASB12
10009	400	61/2.85	1	4995	37	41.0	45.8	18	TASB14
10010	500	61/3.20	1	6320	40.5	45.5	50.5	20	TASB17
10011	630	127/2.52	1	7840	44.6	49.6	54.8	TC9	TASB19

BS6622 11KV PVC SINGLE CORE SCREENED CABLE – ELECTRICAL CHARACTERISTICS

CONDUCTOR SIZE	MAXIMUM CONDUCTOR DC RESISTANCE AT (20°C Ω/Km)	CONDUCTOR AC RESISTANCE AT MAX OPERATING TEMPERATURE AND 50HZ (20°C Ω/KM)	CAPACITANCE mF/Km	CHARGING CURRENT (A/Km)	DIELECTRIC LOSSES (W/Km)	RESISTANCE AT 50HZ (Ω/KM)	CONDUCTOR S.C.C FOR 1 SEC (KA)	SCREEN S.C.C FOR 1 SEC (KA)	CURRENT RATING		
									LAI D IN GROUND A	LAI D IN DUCT A	LAI D IN FREE AIR A
70	0.268	0.342	0.303	0.605	15.35	0.127	10.01	0.3	277	227	313
95	0.193	0.247	0.332	0.662	16.81	0.122	13.585	0.3	329	277	376
120	0.153	0.196	0.362	0.723	18.37	0.119	17.16	0.3	370	308	430
150	0.124	0.159	0.397	0.793	20.15	0.115	21.45	0.4	412	345	484
185	0.0991	0.128	0.43	0.859	21.81	0.111	26.455	0.4	460	390	546
240	0.0754	0.098	0.483	0.964	24.47	0.107	34.32	0.4	520	451	629
300	0.0601	0.078	0.535	1.068	27.13	0.103	42.9	0.5	571	507	708
400	0.047	0.062	0.592	1.181	30.00	0.101	57.2	0.5	609	564	777
500	0.0366	0.049	0.666	33.76	33.76	0.097	71.5	0.6	661	631	863
630	0.0283	0.039	0.76	1.516	38.51	0.095	90.09	0.6	707	698	945
800	0.0221	0.032	0.849	1.694	43.03	0.092	114.4	0.7	750	764	1032

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

ELECTRICAL DATA:

Maximum conductor operating temperature: 90°C
Maximum screen operating temperature: 80°C
Maximum conductor temperature during S.C: 250°C

LAYING CONDITIONS AT TREFOIL FORMATION ARE AS BELOW:

Soil thermal resistivity: 120°C. Cm/Watt
Burial depth: 0.5m
Ground temperature: 15°C
Air temperature: 25°C
Frequency: 50Hz

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.