

624*Y SURFACE WIRING, TWIN AND EARTH - PVC CABLE



APPLICATION

Domestic wiring cable. This cable has a bare protective conductor plus 1, 2 or 3 cores. Used for fixed installations in dry or damp premises clipped direct to surface, on trays or in free air. Where mechanical protection is required, it can be laid in conduit or trunking.

CABLE STANDARDS

Flame propagation to BS EN 50265

BSEN 50363-3

BS6004

BASEC Approved

CONSTRUCTION

Conductor

Upto 4mm²: Class 1 Solid Annealed Compacted Circular Copper Conductor

From 4mm²: Class 2 Stranded Plain Annealed Compacted Circular Copper Conductor

Insulation: PVC

Sheath: PVC

Sheath Colour: Grey

CHARACTERISTICS

Voltage Rating: 300/500 Volts

Temperature Rating: -5°C to +70°C

Minimum Bending Radius:

As per cable manufacturer datasheet

CORE IDENTIFICATION

1 Core: Brown

2 Core: Brown Brown

2 Core: Brown Blue

3 Core: Brown Black Grey

Should not be installed at temperatures below 0°C or above +60°C

624*Y SURFACE WIRING, TWIN AND EARTH - PVC CABLE - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NUMBER OF CORES	CPC SIZE (MM ²)	WEIGHT (KG/KM)	OVERALL DIAMETER (MM)
6241Y1	1	1/1.13	1	1	49	4.15 X 5.40
6241Y1/5	1.5	1/1.37	1	1	51	4.65 X 5.80
6242Y1	1	1/1.13	2	1	69	4.10 X 8.65
6243Y1	1	1/1.13	3	1	92	4.60 X 10.20
6242Y1/5	1.5	1/1.38	2	1	85	4.55 X 8.80
6242Y1/5BRBR	1.5	1/1.38	2	1	85	4.55 X 8.80
6242Y2/5	2.5	1/1.77	2	1.5	120	5.40 X 10.50
6243Y1/5	1.5	1/1.37	3	1	115	4.75 X 11.45
6243Y2/5	2.5	1/1.77	3	1.5	170	5.45 X 13.40
6242Y4	4	7/0.85	2	1.5	17	6.10 X 12.00
6242Y6	6	7/1.04	2	2.5	24	6.90 X 13.80
6242Y10	10	7/1.35	2	4	390	8.40 X 18.50
6242Y16	16	7.1.70	2	6	560	9.70 X 20.60

624*Y TWIN AND EARTH - CARRYING CAPACITY (AMPERES) & VOLTAGE DROP

NOMINAL CROSS SECTIONAL AREA MM ²	REFERENCE METHOD A (IN CONDUIT IN WALL)	REFERENCE METHOD C (CLIPPED DIRECT)	VOLTAGE DROP MV/A/M
1	11.5	16	44
1.5	14.5	20	29
2.5	20	27	18
4	26	37	11
6	32	47	7.3
10	44	64	4.4
16	57	85	2.8

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS.

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.