


FGT COPPER PVC MULTICORE CLASS 2 CABLE



APPLICATION

Power distribution cable for signal operations. With Water Blocking Tape to prevent water ingress and built in fibre glass tape to make it rodent-proof.

CABLE STANDARDS

Conductor to BS EN 60228 (previously BS 6360)
 XLPE Insulation to BS7655-1-3
 BS EN 60811-1
 IEC 60502-1
 Network Rail Specification NR/L2/SIGELP/27408

CONSTRUCTION

Conductor:
Up to 25mm²: Class 1 solid, copper circular or sector shaped conductor
35mm² and above: Class 2 Stranded copper sector shaped

Insulation: Cross-Linked Polyethylene (XLPE)

Anti Rodent Protection: Fibre glass woven tape (FGT)

Water Blocking: Water blocking tape placed under and over the FGT anti rodent protection

Moisture Barrier: Aluminium/polymer laminate tape

Sheath: Black Poly Vinyl Chloride (PVC)

CHARACTERISTICS

Voltage Rating: 600/1000 Volts
Temperature Limits: -25°C to +90°C

CORE IDENTIFICATION

2 Core: Brown Black
3 Core: Brown Black Blue
4 Core: Brown Black Grey Red

FGT COPPER PVC MULTICORE CLASS 2 CABLE - DIMENSIONS

CCC CODE	NR CODE	CONDUCTOR SIZE (MM ²)	NO OF CORES	WEIGHT (KG/KM)	OVERALL DIAMETER (MM)
FGT2X10WBCU	006/186019	10	2	700	23
FGT2X16WBCU	006/186020	16	2	880	24
FGT2X25WBCU	006/186021	25	2	900	25
FGT2X35WBCU	006/186022	35	2	1160	26
FGT2X50WBCU	006/186023	50	2	1430	28
FGT2X70WBCU	006/186024	70	2	1920	31
FGT2X95WBCU	006/186025	95	2	2480	33
FGT2X120WBCU	006/186026	120	2	2980	36
FGT3X10WBCU	-	10	3	720	23
FGT3X16WBCU	-	16	3	935	26
FGT3X25WBCU	-	25	3	1240	28
FGT3X35WBCU	-	35	3	1500	29
FGT3X50WBCU	-	50	3	1885	31
FGT3X70WBCU	-	70	3	2610	33
FGT3X95WBCU	-	95	3	3390	36
FGT3X120WBCU	-	120	3	4115	39
FGT4X10WBCU	-	10	4	795	26
FGT4X16WBCU	-	16	4	1075	28
FGT4X25WBCU	-	25	4	1470	31
FGT4X35WBCU	-	35	4	1900	32
FGT4X50WBCU	-	50	4	2375	35
FGT4X70WBCU	-	70	4	3285	36
FGT4X95WBCU	-	95	4	4330	40
FGT4X120WBCU	-	120	4	5375	44

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.