

ARCTIC GRADE FLEXIBLE CORDS



APPLICATION

Arctic grade cable manufactured to BS6004. The British standard cable will remain flexible to as low as -40 degrees celsius, which makes it ideal for indoor or outdoor use to power portable tools or temporary traffic lights.

CABLE STANDARDS

BS EN 50265
 BS 6004

CONSTRUCTION

Conductor: Plain annealed flexible stranded copper conductor

Insulation: Polyvinyl Chloride (PVC)

Sheath: Polyvinyl Chloride (PVC)

CHARACTERISTICS

Voltage Rating: 300/500 Volts

Temperature Rating: Flexing -40°C to +70°C

Minimum Bending Radius: As per cable manufacturer datasheet

CORE IDENTIFICATION

3 Core: ■ Brown ■ Blue ■ Green/Yellow

4 Core: ■ Brown ■ Black ■ Grey
■ G/Y

Sheath: ■ Blue ■ Yellow

Should not be installed at temperatures below 0°C or above +60°C

ARCTIC GRADE FLEXIBLE CORDS - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NUMBER OF CORES	WEIGHT (KG/KM)	OVERALL DIAMETER (MM)	GLAND SIZE
3183AG1/5	1.5	30/0.25	3	90	8.2	20S
3184AG1/5	1.5	30/0.25	4	130	9.55	20S
3183AG2/5	2.5	50/0.25	3	180	10.15	20S
3184AG2/5	2.5	50/0.25	4	220	11.3	20
3183AG4	4	56/0.30	3	240	11.4	20
3183AG6	6	76/0.30	3	315	13.2	20
6181B16	16	7/1.04	1	225	10.5	20S
6181B25	25	7/2.14	1	340	12.5	20
6181B35	35	7/2.52	1	440	13.5	25

ARCTIC GRADE FLEXIBLE CORDS- ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA MM ²	REFERENCE METHOD A (IN CONDUIT IN WALL)	REFERENCE METHOD C (CLIPPED DIRECT)	VOLTAGE DROP MV/A/M
1	11	20	44
1.5	14.5	27	29
2.5	20	31	18
4	26	42	12
6	34	53	7.9

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.