


BRAIDED TOUGH RUBBER SHEATH FLEXIBLE CORDS (HOFR)



APPLICATION

Braided Tough rubber and flexible cord cable is suitable for installing in damp environments. It is designed for temporary building sites as the upper braiding prevents earth leakage and offers mechanical protection. Heat and oil resistant and flame retardant (HOFR)

CABLE STANDARDS

BS6500/75
BS6007/75
Flame Propagation to BS 4066 PT1
Flame Propagation to IEC 332 PT1

CONSTRUCTION

Conductor: Flexible Tinned Annealed Copper Conductors
Insulation: Heavy duty Polychloropene (PCP)
Screen: Tinned Copper Wire Braid
Sheath: Heavy duty Polychloropene (PCP)
Sheath Colour: Black

CHARACTERISTICS

Voltage Rating:
300/500 Volts grade to BS6500/75
450/750 Volts grade to BS6007/75
Temperature Limits: Fixed: -25°C to +60°C
Minimum Bending Radius: As per cable manufacturer datasheet

CORE IDENTIFICATION

2 Core: Brown Blue
3 Core: Brown Blue G/Y
4 Core: Brown Black Grey
G/Y

Should not be installed at temperatures below 0°C

BRAIDED TOUGH RUBBER SHEATH FLEXIBLE CORDS - DIMENSIONS

CCC CODE	CONDUCTOR SIZE (MM ²)	STRANDING (MM)	NO. OF CORES	WEIGHT (KG/KM)	OVERALL DIAMETER (MM)	GLAND SIZE (MM)
3802P1	1	32/0.20	2	170	11.1	20/16
3803P1	1	32/0.20	3	200	11.4	20/16
3804P1	1	32/0.20	4	230	12.1	20/16
3802P1/5	1.5	30/0.25	2	225	12.3	20/16
3803P1/5	1.5	30/0.25	3	270	13.1	20S
3804P1/5	1.5	30/0.25	4	320	14.2	20S
3802P2/5	2.5	50/0.25	2	300	14.8	20S
3803P2/5	2.5	50/0.25	3	350	15.6	20
3804P2/5	2.5	50/0.25	4	420	17	20
3803P4	4	56/0.30	3	715	21.3	25
3804P4	4	56/0.30	4	865	23.6	25

BRAIDED TOUGH RUBBER SHEATH CORDS – ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA MM ²	REFERENCE METHOD A (IN CONDUIT IN WALL)	REFERENCE METHOD C (CLIPPED DIRECT)	VOLTAGE DROP MV/A/M
1	11	20	44
1.5	14.5	27	29
2.5	20	31	18
4	26	42	12
6	34	53	7.9

THE ABOVE IS IN ACCORDANCE WITH 18TH EDITION OF IET WIRING REGULATIONS

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION.