




LSZH ELECTRIC VEHICLE CHARGING & 4 PAIR FTP CAT5e CABLE



APPLICATION

This cable is for use in the installation of electric vehicle charge points. This is a combined armoured 3 core power and 4 pair CAT5e Data cable in a double sheathed design for extra protection.

Whilst designed for use in electric vehicle chargepoints, the cable is suitable for other installations where power and CAT5e Data cable is required.

CONSTRUCTION - POWER CABLE

Conductor: Class 5 Flexible Stranded Copper
Insulation: XLPE (Cross Link Polyethelene)
Bedding: LSZH (Low Smoke Zero Halogen)
Sheath: LSZH (Low Smoke Zero Halogen)
Sheath Colour: **Black**

CONSTRUCTION - CAT5e CABLE

Conductor: Class 1 Solid Copper
Insulation: HDPE
Screen: Aluminium Foil & drain wire
CAT5e Sheath: LSZH
Sheath Colour: **Violet**

CABLE STANDARDS

IEC 60228	IEC60754-1
IEC 60502-1	IEC61034-2
IEC 60332-1-2	IEC60332-3-24 CAT C

CHARACTERISTICS

Voltage Rating:	600 - 1000 Volts
Test Voltage:	4kV
Temperature Limits:	-30°C to +80°C
Minimum Bending Radius:	As per cable manufacturer datasheet

CORE IDENTIFICATION

3 Core: **Brown Blue Green/Yellow**

CAT5e Sheath: PVC (Poly Vinyl Chloride)

Pair 1:	Blue Blue/White
Pair 2:	Orange Orange/White
Pair 3:	Green Green/White
Pair 4:	Brown Brown/White

Should not be installed at temperatures below 0°C

LSZH ELECTRIC VEHICLE CHARGING & 4 PAIR FTP CAT5e CABLE - CABLE DIMENSIONS

CCC CODE	CONDUCTOR SIZE (mm ²)	STRANDING	NO OF CORES	WEIGHT (Kg/Km)	OVERALL DIAMETER (mm)
CONNECTEV3X4LSZH	4	Class 5	3+CAT5e	455	17.6
CONNECTEV3X6LSZH	6	Class 5	3+CAT5e	740	19.5

For more information contact:
01642 241 133