

LOW VOLTAGE LSZH ALUMINIUM WAVEFORM CABLE



APPLICATION

Used by Distribution Network Operators (DNOs) such as UKPN, WPD, ENW, NPG, SSE etc. Aluminium Waveform cable is used as an energy supply cable most commonly found in power station distribution, panel boards and street lighting areas where mechanical protection is required. It consists of 3 or 4 solid aluminium conductors in sector shape with a copper conductor in a concentric waveform lay.

CONSTRUCTION

Conductor: Class 1 solid aluminium conductor
Insulation: Cross-Linked Polyethylene (XLPE)
Separator: Binding tape
Bedding: Extruded Rubber Compound
Waveform Conductor: Plain Copper wire Screen
Sheath: Low smoke Zero Halogen (LSZH)
Sheath Colour: ■ Orange

CABLE STANDARDS

BS 7870-3-50
BS 7870-1
Flame Retardant to IEC/EN 60228
Low smoke to IEC/EN 61034-1/2

CHARACTERISTICS

Voltage Rating: 600/1000 Volts
Minimum Bending Radius:
As per cable manufacturer datasheet

CORE IDENTIFICATION

3 Core: ■ Brown ■ Black ■ Grey
4 Core: ■ Brown ■ Black ■ Grey ■ Blue

LSZH ALUMINIUM WAVEFORM CABLE – DIMENSIONS

CCC CODE	NUMBER OF CORES	CONDUCTOR SIZE (MM ²)	CONCENTRIC WAVEFORM CONDUCTOR NUMBER OF WIRES			OVERALL DIAMETER (MM)	WEIGHT (KG/KM)
			NUMBER OF WIRES	WIRE DIAMETER	LENGTH OF LAY		
WAVEFORM 3X95LSF	3	95	22	1.85	250	36	1980
WAVEFORM 3X185LSF	3	185	41	1.85	300	43	3500
WAVEFORM 3X300LSF	3	300	41	1.85	440	53	4900
WAVEFORM 4X95LSF	4	95	22	1.85	250	36	2300
WAVEFORM 4X185LSF	4	185	41	1.85	300	48	4200
WAVEFORM 4X300LSF	4	300	41	1.85	440	60	6100

LSZH ALUMINIUM WAVEFORM CABLE – ELECTRICAL CHARACTERISTICS

Nominal Cross Section mm ²	95	185	300
Maximum DC resistance of phase conductor @ 20°C (Ω/km)	0.320	0.164	0.100
Maximum DC resistance of neutral/earth conductor@ 20°C (Ω/km)	0.320	0.164	0.164
Maximum AC resistance of conductor@ 90°C (Ω/km)	0.411	0.211	0.130
Approximate Reactance@ 50Hz (Ω/km)	0.073	0.073	0.072
Approximate volt drop (mV/A/m)	0.410	0.330	0.250
Zero Phase Sequence Resistance (Ω/km)	0.241	0.124	0.084
Zero Phase Sequence Reactance (Ω/km)	0.086	0.077	0.074
Nominal internal diameter of ducts (mm)	70.0	90.0	110.0
Current Ratings			
Direct in ground (Amps)	244	353	461
In Ducts (Amps)	227	328	429
In Air (Amps)	232	364	508
Current rating conditions			
Ground temperature	15°C		
Ambient Air temperature	25°C		
Depth of burial (to top of cable)	450mm		
Thermal resistance of soil	1.2°C m/W		

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.