

National Grid (NGED) Approved Triplex Cable - 11kV, XLPE, MDPE - 95mm² to 300mm²



Description

National Grid (NGED) approved specification medium voltage aluminium power cable for connections from electrical grid to sub-main developments. Suitable for power networks, underground, outdoors and installation in cable ducting.

Key Features



Voltage Rating
6.35kV / 11kV (11kV)



Minimum Bending Radius
12 x Overall Diameter



Temperature Limits
Temperature Range: 0°C to +90°C

Core Colours

Single Core Triplex

Brown Black Grey Tapes

Standards

- DNO Cable approved for NGED use.
- BS 7870-4.10
- BS EN/IEC 60228

Construction

- **Conductor:** Solid Aluminium
- **Conductor Screen:** Bonded semi conductive material
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Insulation Screen:** Semi-conductive material (bonded)
- **Longitudinal Waterblocking:** Semi-conductive swellable tape
- **Screen:** Copper Wires & Helical Equalising Copper Tape
- **Longitudinal Water Blocking:** Water blocking tape
- **Sheath:** Medium Density Polyethylene (MDPE)
- **Sheath Colour:** Red: UV Stabilised

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

National Grid (NGED)Approved Triplex Cable - 11kV, XLPE, MDPE - 95mm² to 300mm² - Dimensions

Reference	size
NGED11KVTRIP3X300AL	300

TRIPLEX CABLE – CURRENT CARRYING CAPACITY

MAX VOLTAGE RATING	NOMINAL CROSS SECTIONAL AREA (MM ²)	IN GROUND AMPS	IN DUCTS AMPS	IN AIR AMPS
		SEE NOTE 1*	SEE NOTE 2**	SEE NOTE 3***
11kV	95	221	230	280
11kV	185	317	303	424
11kv	300	437	397	577

Note 1* Ground Temperature = 20°C, Depth = 0.8m, Thermal resistivity of soil -1.5K.m/w

Note 2** As Note 1* but 1 cable per duct

Note 3*** Ambient Temperature = 30°C

TRIPLEX CABLE 11KV – ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA	MAXIMUM DC RESISTANCE OF CONDUCTOR AT 20°C	MAXIMUM AC RESISTANCE OF CONDUCTOR AT 90°C	REACTANCE AT 50HZ	CAPACITANCE	1 SECOND SHORT CIRCUIT RATING OF CONDUCTOR	1 SECOND SHORT CIRCUIT RATING OF METALLIC SCREEN
(MM ²)	(OHMS/KM)	(OHMS/KM)	(OHMS/KM)	(µF/KM)	(kA)	(kA)
95	0.32	0.411	0.12	0.32	8.9	5.3
185	0.164	0.211	0.11	0.41	17.4	10.3
300	0.1	0.13	0.13	0.5	28.3	10.3

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.