125amp 230v and 415v Industrial Extension Leads 90°c ExtremeFlex90®

Description

Bespoke 125A industrial extension leads manufactured using ExtremeFlex90® 90°C rubber cable and fitted with Mennekes plugs and sockets. Designed for high-current power connections in industrial, commercial and temporary power applications.
Available cut to length to suit individual requirements, with the flexible rubber cable providing a durable solution for demanding working environments.

Key Features

Minimum Bending Radius
(Less than 12mm²): 3 X Overall Diameter
(More than 12mm²): 4 X Overall Diameter

Flame Retardancy
BS EN 60332-1-2

Temperature Limits
Temperature Range: -40 to 90°C

Core Colours

3 Core: Brown | Blue | Green Yellow

5 Core: Brown | Black | Grey | Blue | Green Yellow

Standards

- BS EN 60811-2-1
- UV Resistant Sheath
- BS EN 60228
- Conforms to H07RN-F
- BS EN/IEC 60332-1-2
- BS EN 50363
- AD8 water resistance

Construction

- **Conductor**: Class 5 flexible, stranded copper
- **Insulation**: Ethylene Propylene Rubber (EPR)
- **Outer Sheath**: UV Resistant Chlorinated Polyethylene (CPE)
- **Sheath Colour**: Black

Training & Testing Lab

AN ISO/IEC 17025 ACCREDITED FACILITY

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing.

ISO/IEC 17025 Accredited Testing Laboratory
UKAS TESTING 31196

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

CLEVELAND CABLE COMPANY

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

125amp 230v and 415v Industrial Extension Leads 90°c ExtremeFlex90® - Dimensions

Reference	Voltage/Colour	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter(Lower)	Overall Diameter(Upper)	Length(m)
6383P25EXT5M/125	230V 2P+E Pin Blue	25	3	196/0.40	1.4	3.8	27.3	30.2	5
6383P25EXT10M/125	230V 2P+E Pin Blue	25	3	196/0.40	1.4	3.8	27.3	30.2	10
6383P25EXT15M/125	230V 2P+E Pin Blue	25	3	196/0.40	1.4	3.8	27.3	30.2	15
6383P25EXT20M/125	230V 2P+E Pin Blue	25	3	196/0.40	1.4	3.8	27.3	30.2	20
6383P25EXT25M/125	230V 2P+E Pin Blue	25	3	196/0.40	1.4	3.8	27.3	30.2	25
6385P25EXT5M/125	415V 3P+N+E Pin Red	25	5	196/0.40	1.4	4.5	33.4	37.0	5
6385P25EXT10M/125	415V 3P+N+E Pin Red	25	5	196/0.40	1.4	4.5	33.4	37.0	10
6385P25EXT15M/125	415V 3P+N+E Pin Red	25	5	196/0.40	1.4	4.5	33.4	37.0	15
6385P25EXT20M/125	415V 3P+N+E Pin Red	25	5	196/0.40	1.4	4.5	33.4	37.0	20
6385P25EXT25M/125	415V 3P+N+E Pin Red	25	5	196/0.40	1.4	4.5	33.4	37.0	25
6383P35EXT5M/125	230V 2P+E Pin Blue	35	3	276/0.40	1.4	3.8	29.3	33.5	5
6383P35EXT10M/125	230V 2P+E Pin Blue	35	3	276/0.40	1.4	3.8	29.3	33.5	10
6383P35EXT15M/125	230V 2P+E Pin Blue	35	3	276/0.40	1.4	3.8	29.3	33.5	15
6383P35EXT20M/125	230V 2P+E Pin Blue	35	3	276/0.40	1.4	3.8	29.3	33.5	20
6383P35EXT25M/125	230V 2P+E Pin Blue	35	3	276/0.40	1.4	3.8	29.3	33.5	25
6385P35EXT5M/125	415V 3P+N+E Pin Red	35	5	276/0.40	1.4	4.6	36.9	40.7	5
6385P35EXT10M/125	415V 3P+N+E Pin Red	35	5	276/0.40	1.4	4.6	36.9	40.7	10
6385P35EXT15M/125	415V 3P+N+E Pin Red	35	5	276/0.40	1.4	4.6	36.9	40.7	15
6385P35EXT20M/125	415V 3P+N+E Pin Red	35	5	276/0.40	1.4	4.6	36.9	40.7	20
6385P35EXT25M/125	415V 3P+N+E Pin Red	35	5	276/0.40	1.4	4.6	36.9	40.7	25
6383P50EXT5M/125	230V 2P+E Pin Blue	50	3	396/0.40	1.6	4.5	35.0	38.7	5
6383P50EXT10M/125	230V 2P+E Pin Blue	50	3	396/0.40	1.6	4.5	35.0	38.7	10
6383P50EXT15M/125	230V 2P+E Pin Blue	50	3	396/0.40	1.6	4.5	35.0	38.7	15

Reference	Voltage/Colour	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Diameter(Lower)	Overall Diameter(Upper)	Length(m)
6383P50EXT20M/125	230V 2P+E Pin Blue	50	3	396/0.40	1.6	4.5	35.0	38.7	20
6383P50EXT25M/125	230V 2P+E Pin Blue	50	3	396/0.40	1.6	4.5	35.0	38.7	25
6385P50EXT5M/125	415V 3P+N+E Pin Red	50	5	396/0.40	1.6	5.2	43.3	47.2	5
6385P50EXT10M/125	415V 3P+N+E Pin Red	50	5	396/0.40	1.6	5.2	43.3	47.2	10
6385P50EXT15M/125	415V 3P+N+E Pin Red	50	5	396/0.40	1.6	5.2	43.3	47.2	15
6385P50EXT20M/125	415V 3P+N+E Pin Red	50	5	396/0.40	1.6	5.2	43.3	47.2	20
6385P50EXT25M/125	415V 3P+N+E Pin Red	50	5	396/0.40	1.6	5.2	43.3	47.2	25

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.