

13A Plug - PowerCon Extension Lead (318-Y) Black

Description

Bespoke 13A Plug - PowerCon extension lead adaptor, cut to length, available in our 318-Y cable. Designed for secure and reliable power connections. Durable, high-quality solutions for professional and commercial use.

Key Features



Voltage Rating
300/500 Volts



Minimum Bending Radius
Fixed: 6 x overall diameter
Flexing: 8 x overall diameter



Flame Retardancy
BS EN 60332-1-2



Temperature Limits
Fixed: +5°C to +70°C

Standards

- Conforms to H05VV-F
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228

Construction

- **Conductor:** Class 5 Flexible Copper Conductor
- **Insulation:** Polyvinyl Chloride (PVC)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



13A Plug - PowerCon Extension Lead (318-Y) Black - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)
3183Y1/5EXT13-PC3	1.5	3	30/0.25
3183Y1/5EXT13-PC5	1.5	5	30/0.25
3183Y1/5EXT13-PC10	1.5	10	30/0.25

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.