318*TQ Flexible Mains & Control Cable - EPR, CSP - 0.75mm² to 2.5mm²



Description

Our range of flexible TQ cables is designed for fixed wiring installations. It is a range of unarmoured cable designed to prevent the risk of electric shock in the event of fault or surge. Our TQ cable is suitable as a flexible marine cable, both on and offshore. This range of 300/500V (refer to core size in Characteristics) is heat and oil resistant, and flame retardant (HOFR).

Datasheet must be used in conjunction with 18th edition IET wiring regulations.

Key Features

Voltage Rating
300/500 Volts

Minimum Bending Radius
6 x overall diameter

Flame Retardancy
BS EN/IEC 60332-1-2

Temperature Limits
Temperature Range: -40°C to +90°C

Core Colours

2 core - Blue, Brown

3 core - Blue, Brown, Green Yellow

4 core - Brown, Black, Grey, Green Yellow

5 core - Blue, Brown, Black, Grey, Green Yellow

6 core and above - Black with White numbers plus Green Yellow

Standards

- BS EN 50525-2-21
- BS EN/IEC 60332-1-2
- BS EN 50363-2-1
- BS EN/IEC 60228
- Conforms to H05BN4-F

Construction

- **Conductor**: Class 5 flexible stranded copper conductor
- **Insulation**: Ethylene Propylene Rubber (EPR)
- **Outer Sheath**: Chlorosulphonated polyethylene (CSP)
- **Sheath Colour**: Black

Training & Testing Lab

AN ISO/IEC 17025 ACCREDITED FACILITY

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing.

ISO/IEC 17025 Accredited Testing Laboratory
UKAS TESTING 31196

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

CLEVELAND CABLE COMPANY

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

318*TQ Flexible Mains & Control Cable - EPR, CSP - 0.75mm² to 2.5mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Size
3182TQ/75	0.75	2	24/0.20	5.7	58	7.4
3183TQ/75WH	0.75	3	24/0.20	6.2	72	8.1
3184TQ/75WH	0.75	4	24/0.20	6.2	72	8.1
3182TQ1	1	2	32/0.20	6.1	80	8
3183TQ1	1	3	32/0.20	6.5	90	8.5
3184TQ1	1	4	32/0.20	7.1	110	9.3
3181TQ1/5	1.5	1	30/0.25	5.7	38	7.1
3182TQ1/5	1.5	2	30/0.25	7.6	115	7.6
3183TQ1/5	1.5	3	30/0.25	8	135	10.4
3184TQ1/5	1.5	4	30/0.25	9	170	11.6
3185TQ1/5	1.5	5	30/0.25	11.2	200	14.4
3186TQ1/5	1.5	6	30/0.25	13.4	335	17.2
3187TQ1/5	1.5	7	30/0.25	14.6	366	18.2
3180/12TQ1/5	1.5	12	30/0.25	17.6	410	22.4
3180/18TQ1/5	1.5	18	30/0.25	19.8	570	24.3
3180/19TQ1/5	1.5	19	30/0.25	21.4	710	26.7
3180/27TQ1/5	1.5	27	30/0.25	25.3	920	25.3
3181TQ2/5	2.5	1	50/0.25	6.3	41	7.9
3182TQ2/5	2.5	2	50/0.25	9	160	11.6
3183TQ2/5	2.5	3	50/0.25	9.6	195	12.4
3184TQ2/5	2.5	4	50/0.25	10.7	245	13.8
3185TQ2/5	2.5	5	50/0.25	13.3	300	17
3187TQ2/5	2.5	7	50/0.25	17.2	424	21
3180/12TQ2/5	2.5	12	50/0.25	20.6	600	26.2
3180/16TQ2/5	2.5	16	50/0.25	23.8	780	28.4
3180/20TQ2/5	2.5	20	50/0.25	26.4	1050	31.2
3180/27TQ2/5	2.5	27	50/0.25	30.1	1390	35.4
3180/37TQ2/5	2.5	37	50/0.25	35	1720	40.9

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.