

6181B Mains Cable - BS8573, XLPE, LSZH - 50mm² to 1000mm²



Description

6181B is a low smoke halogen single core cable, double insulated with a voltage rating of 600/1000V. General surface wire cable for fixed installation, domestic and light industrial use. Available in Blue and Brown core, with a black sheath. Comes in sizes 500mm² - 1000mm². As this cable is used internally, it is covered by current CPR regulations.

Key Features



Voltage Rating
600/1000 Volts



Minimum Bending Radius
12 x Overall Diameter



Flame Retardancy
BS EN/IEC 60332-1



Temperature Limits
Temperature Range: 0°C to +90°C

Core Colours

All sizes available in Brown and Blue

Standards

- BS EN/IEC 60228
- BS EN/IEC 60332-1
- IEC/EN 60754-1/2
- IEC 61034-1
- BS8573 / IEC 60502-1

Construction

- **Conductor:** Class 2 stranded copper conductor
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Outer Sheath:** Low Smoke Zero Halogen (LSZH)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance.

ecovadis

6181B Mains Cable - BS8573, XLPE, LSZH - 50mm² to 1000mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
6181B50	50	1	19/1.78	13	525	0.6	25
6181B70	70	1	19/2.14	15.5	730	0.7	25
6181B95	95	1	19/2.52	18	990	0.7	25
6181B120	120	1	37/2.03	19.5	1230	0.8	32
6181B150	150	1	37/2.25	21.5	1525	0.9	32
6181B185	185	1	37/2.52	24	1885	1	32
6181B240	240	1	61/2.25	27	2440	1.1	40
6181B300	300	1	61/2.52	29.5	3045	1.2	40
6181B400	400	1	61/2.52	33	3855	1.4	50S
6181B500	500	1	61/3.20	37.5	4950	1.6	50S
6181B630	630	1	127/2.52	42	6345	1.8	50
6181B800	800	1	127/2.85	47.5	8140	2	63S
6181B1000	1000	1	127/2.85	53	9860	TC9	63



TABLE 4E1A

CURRENT-CARRYING CAPACITY (amperes)

Ambient temperature: 30°C
Conductor operating temperature: 90°C

Conductor cross sectional area	Reference Method A (enclosed in conduit in thermally insulating wall etc.)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method F (in free air or on a perforated cable tray etc horizontal or vertical etc) Touching			Reference Method G (in free air) Spaced by one cable diameter		
	2 cables single phase AC or DC	3 or 4 cables, three-phase AC	2 cables single phase AC or DC	3 or 4 cables, three-phase AC	2 cables single phase AC or DC flat and touching	3 or 4 cables, three-phase AC flat and touching or trefoil	2 cables single phase AC or DC flat	3 cables, three-phase AC flat	3 cables, three-phase AC trefoil	2 cables, single-phase AC or DC or 3 cables three-phase AC flat	Horizontal	Vertical
										mm ²	A	A
1	14	13	17	15	19	17.5	-	-	-	-	-	-
1.5	19	17	23	20	25	23	-	-	-	-	-	-
4	35	31	42	37	46	41	-	-	-	-	-	-
6	45	40	54	48	59	54	-	-	-	-	-	-
10	61	54	75	66	81	74	-	-	-	-	-	-
16	81	73	100	88	109	99	-	-	-	-	-	-
25	106	95	133	117	143	130	161	141	135	182	161	161
35	131	117	164	144	176	161	200	176	169	226	201	201
50	158	141	198	175	228	209	242	216	207	275	246	246
70	200	179	253	222	293	268	310	279	268	353	318	318
95	241	216	306	269	355	326	377	342	328	430	389	389
120	278	249	354	312	413	379	437	400	383	500	454	454
150	318	285	393	342	476	436	504	464	444	577	527	527
185	362	324	449	384	545	500	575	533	510	661	605	605
240	424	380	528	450	644	590	679	634	607	781	719	719
300	486	435	603	514	743	681	783	736	703	902	833	833
400	-	-	683	584	868	793	940	868	823	1085	1008	1008
500	-	-	783	666	990	904	1083	998	946	1253	1169	1169
630	-	-	900	764	1130	1033	1254	1151	1088	1454	1362	1362
800	-	-	-	-	1288	1179	1358	1275	1214	1581	1485	1485
1000	-	-	-	-	1443	1323	1520	1436	1349	1775	1671	1671

Where it is intended to connect the cables in this table to equipment or accessories designed to operate at a temperature lower than the maximum operating temperature of the cable, the cables should be rated at the maximum operating temperature of the equipment or accessory (see Regulation 512.1.5). Where it is intended to group a cable in this table with other cables, the cable should be rated at the lowest of the maximum operating temperatures of any of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying capacity and voltage drop.



TABLE 4E1B

VOLTAGE DROP (per ampere per metre)

Conductor operating temperature: 90°C

Conductor cross sectional area	2 cables, DC	2 cables, single-phase AC						3 or 4 cables, three-phase AC					
		Reference Methods A & B (enclosed in conduit or trunking)			References Methods C, F & G (clipped direct, on tray or in free air)			Reference Methods A & B (enclosed in conduit or trunking)			Reference Methods C, F & G (clipped direct, on tray or in free air)		
		Cables touching		Cables spaced*	Cables touching		Cables spaced*	Cables touching, Trefoil		Cables touching, Flat	Cables spaced* Flat		
(mm ²)	(mV/ A/m)	(mV/A/m)		(mV/A/m)	(mV/A/m)		(mV/A/m)	(mV/A/m)		(mV/A/m)	(mV/A/m)		(mV/A/m)
1	46	46		46	46		40	40		40	40		40
1.5	31	31		31	31		27	27		27	27		27
2.5	19	19		19	19		16	16		16	16		16
4	12	12		12	12		10	10		10	10		10
6	7.9	7.9		7.9	7.9		6.8	6.8		6.8	6.8		6.8
10	4.7	4.7		4.7	4.7		4.0	4.0		4.0	4.0		4.0
16	2.9	2.9		2.9	2.9		2.5	2.5		2.5	2.5		2.5
		R	X	Z	R	X	Z	R	X	Z	R	X	Z
25	1.850	1.850	0.310	1.900	1.850	0.190	1.850	1.850	0.280	1.850	1.600	0.270	1.650
35	1.350	1.350	0.290	1.350	1.350	0.180	1.350	1.350	0.270	1.350	1.150	0.250	1.150
50	0.990	1.000	0.290	1.050	0.990	0.180	1.000	0.990	0.270	1.000	0.870	0.250	0.890
70	0.680	0.700	0.280	0.750	0.680	0.175	0.710	0.680	0.260	0.730	0.600	0.240	0.650
95	0.490	0.510	0.270	0.580	0.490	0.170	0.520	0.490	0.260	0.560	0.440	0.230	0.500
120	0.390	0.410	0.260	0.480	0.390	0.165	0.430	0.390	0.250	0.470	0.350	0.230	0.420
150	0.320	0.330	0.260	0.430	0.320	0.165	0.360	0.320	0.250	0.410	0.290	0.230	0.370
185	0.250	0.270	0.260	0.370	0.260	0.165	0.300	0.250	0.250	0.360	0.230	0.230	0.330
240	0.190	0.210	0.260	0.330	0.200	0.160	0.250	0.195	0.250	0.310	0.185	0.220	0.290
300	0.155	0.175	0.250	0.310	0.160	0.160	0.220	0.155	0.250	0.290	0.150	0.220	0.270
400	0.120	0.140	0.250	0.290	0.130	0.155	0.200	0.125	0.240	0.270	0.125	0.220	0.250
500	0.093	0.120	0.250	0.280	0.105	0.155	0.185	0.098	0.240	0.260	0.100	0.220	0.240
630	0.072	0.100	0.250	0.270	0.086	0.155	0.175	0.078	0.240	0.250	0.088	0.210	0.240
800	0.056	-	-	0.072	0.150	0.170	0.064	0.240	0.250	-	0.062	0.130	0.145
1000	0.045	-	-	0.063	0.150	0.165	0.054	0.240	0.240	-	0.055	0.130	0.140

NOTE: * Spacings larger than one cable diameter will result in a larger voltage drop.

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.



CE

