

6181Y Surface Wiring Cable BS6004, PVC - 1mm² to 120mm²



Description

6181Y is a PVC single core cable, double insulated with a voltage rating of 300/500V for up to 35mm. Above 35mm the cable has a voltage rating of 600/1000V. It is a general surface wire cable for fixed installation, domestic and light industrial use. Available in blue and brown cores, sizes from 1mm - 120mm. This cable is BASEC approved to 35mm.

Key Features



Voltage Rating

Up to 35mm²: 300/500V . 50mm² and Above: 600/1000V



Minimum Bending Radius

Up to 6mm²: 4x overall diameter Above 6mm²: 6 x overall diameter



Flame Retardancy BS EN/IEC 60332-1-2



Temperature Limits Temperature Range: -15°C to + 70°C

Core Colours

All sizes available in Brown or Blue





Standards

- BS EN/IEC 60332-1-2
- BS EN/IEC 60228
- Above 35mm² BS 6004/IEC 60502-1
- Upto 35mm2 BS 6004

Construction

- Conductor: Up to 2.5mm: Class 1 solid copper, 4mm Class 2 stranded
- Insulation: Polyvinyl Chloride (PVC)
- Sheath: PVC (Polyvinyl Chloride)
- Sheath Colour: Grey or White

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while $reducing\ carbon\ emissions\ in\ collaboration\ with\ our\ customers\ and\ suppliers.$



Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis



















6181Y Surface Wiring Cable BS6004, PVC - 1mm² to 120mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size	
6181Y1/5B	1.5	1	1/1.38	5.1	36	NONE	20/16	
6181Y2/5B	2.5	1	1/1.78	6	51	NONE	20/16	
6181Y4B	4	1	7/0.85	6.8	75	NONE	20/16	
6181Y6B	6	1	7/1.04	7.4	98	NONE	20/16	
6181Y10B	10	1	7/1.35	8.8	150	NONE	205	
6181Y16B	16	1	7/1.70	10.5	220	0.5	205	
6181Y25B	25	1	7/2.14	12.5	340	0.5	20	
6181Y35B	35	1	7/2.52	13.5	440	0.6	25	
6181Y50B	50	1	19/1.78	14.38	540	0.6	25	
6181Y70B	70	1	19/2.14	15.3	750	0.7	25	
6181Y95B	95	1	19/2.52	17.7	1010	0.7	25	
6181Y120B	120	1	37/2.03	19.3	1250	0.8	32	

















CENELEC



TABLE 4D1A

CURRENT-CARRYING CAPACITY (amperes):

Ambient temperature: 30 °C Conductor operating temperature: 70 °C

Conductor	Reference N		Reference M		Reference	e Method C (clipped	Reference Method F							
cross-	(enclosed in conduit in thermally insulating			n conduit on a trunking etc.)		direct)	(in free air or on a perforated cable tray horizontal or vertical)							
sectional in thermally insulating wall etc)			wall of ill	trunking etc.)				Touching	Spaced by one diameter					
	2 cables, single- phase AC or DC	3 or4 cables, three- phase	2 cables, single- phase AC or DC	3 or4 cables, three- phase	2 cables, single- phase AC or DC flat and	3 or4 cables, three- phase AC flat and touching or	2 cables, single- phase AC or DC flat	3 cables, three- phase AC flat	3 cables, three- phase AC	2 cables, single-phase AC or DC or 3 cables three- phas AC flat				
		AC		AC	touching	trefoil			trefoil	Horizontal	Vertical			
	2	3	4	5	6	7	8	9	10	11	12			
(mm 2)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)			
1	11	10.5	13.5	12	15.5	14	-	-	-	-	-			
1.5	14.5	13.5	17.5	15.5	20	18	-	-	-	-	-			
2.5	20	18	24	21	27	25								
4	26	24	32	28	37	33								
6	34	31	41	36	47	43								
IO	46	42	57	50	65	59								
16	61	56	76	68	87	79								
25	80	73	101	89	114	104	131	114	110	146	130			
35	99	89	125	110	141	129	162	143	137	181	162			
50	119	108	151	134	182	167	196	174	167	219	197			
70	151	136	192	171	234	214	251	225	216	281	254			
95	182	164	232	207	284	261	304	275	264	341	311			
120	210	188	269	239	330	303	352	321	308	396	362			
150	240	216	300	262	381	349	406	372	356	456	419			
185	273	245	341	296	436	400	463	427	409	521	480			
240	321	286	400	346	515	472	546	507	485	615	569			
300	367	328	458	394	594	545	629	587	561	709	659			
400	-	-	546	467	694	634	754	689	656	852	795			
500	-	-	626	533	792	723	868	789	749	982	920			
630	-	-	720	611	904	826	1005	905	855	1138	1070			
800	-	-	-	-	1030	943	1086	1020	971	1265	1188			
1000	-	-	-	-	1154	1058	1216	1149	1079	1420	1337			

















CENELEC



TABLE 4D1B

VOLTAGE DROP (per ampere per metre):

Conductor operating temperature: 70 $^{\circ}\text{C}$

Conductor	2 cables				2 cables, single-phase AC					3 or 4 cables, three-phase AC													
cross-sectional area	DC	Reference Methods A & B (enclosed in conduit or			Reference Methods C & F (clipped direct, on tray or in free air)					Reference Methods A & B (enclosed in conduit or			Reference Methods C & F (clipped direct, on tray or in free air)										
		trunking)		Cables touching			Cables spaced*			trunking)			Cables touching, Trefoil			Cables touching, Flat			Cables spaced*, Flat				
1	2		3			4			5			6			7			8			9		
mm ²	(mV/ Nm)		(mV/Afm)	mV/Afm) (mV/Afm)			(mV/Afm)			(mV/Afm)			(mV/Afm)			(mV/Afm)			(mV/Afm)				
1	44		44			44		44			38			38			38			38			
1.5	29		29			29			29			25			25			25			25		
2.5	18		18			18			18			15			15			15			15		
4	11		11			11			11			9.5			9.5			9.5			9.5		
6	7.3		7.3			7.3			7.3			6.4			6.4			6.4			6.4		
10	4.4		4.4		4.4			4.4		3.8			3.8			3.8			3.8				
16	2.8		2.8			2.8			2.8		2.4			2.4			2.4			2.4			
		r	Х	Z	r	Х	Z	r	Х	Z	r	Х	Z	r	Х	Z	r	X	Z	r	Х	Z	
25	1.75	1.80	0.33	1.80	1.75	0.20	1.75	1.75	0.29	1.80	1.50	0.29	1.55	1.50	0.175	1.50	1.50	0.25	1.55	1.50	0.32	1.55	
35	1.25	1.30	0.31	1.30	1.25	0.195	1.25	1.25	0.28	1.30	1.10	0.27	1.10	1.10	0.170	1.10	1.10	0.24	1.10	1.10	0.32	1.15	
50	0.93	0.95	0.30	1.00	0.93	0.190	0.95	0.93	0.28	0.97	0.81	0.26	0.85	0.80	0.165	0.82	0.80	0.24	0.84	0.80	0.32	0.86	
70	0.63	0.65	0.29	0.72	0.63	0.185	0.66	0.63	0.27	0.69	0.56	0.25	0.61	0.55	0.160	0.57	0.55	0.24	0.60	0.55	0.31	0.63	
95	0.46	0.49	0.28	0.56	0.47	0.180	0.50	0.47	0.27	0.54	0.42	0.24	0.48	0.41	0.155	0.43	0.41	0.23	0.47	0.40	0.31	0.51	
120	0.36	0.39	0.27	0.47	0.37	0.175	0.41	0.37	0.26	0.45	0.33	0.23	0.41	0.32	0.150	0.36	0.32	0.23	0.40	0.32	0.30	0.44	
150	0.29	0.31	0.27	0.41	0.30	0.175	0.34	0.29	0.26	0.39	0.27	0.23	0.36	0.26	0.150	0.30	0.26	0.23	0.34	0.26	0.30	0.40	
185	0.23	0.25	0.27	0.37	0.24	0.170	0.29	0.24	0.26	0.35	0.22	0.23	0.32	0.21	0.145	0.26	0.21	0.22	0.31	0.21	0.30	0.36	
240	0.180	0.195	0.26	0.33	0.185	0.165	0.25	0.185	0.25	0.31	0.17	0.23	0.29	0.160	0.145	0.22	0.160	0.22	0.27	0.160	0.29	0.34	
300	0.145	0.160	0.26	0.31	0.150	0.165	0.22	0.150	0.25	0.29	0.14	0.23	0.27	0.130	0.140	0.190	0.130	0.22	0.25	0.130	0.29	0.32	
400	0.105	0.130	0.26	0.29	0.120	0.160	0.20	0.115	0.25	0.27	0.12	0.22	0.25	0.105	0.140	0.175	0.105	0.21	0.24	0.100	0.29	0.31	
500	0.086	0.110	0.26	0.28	0.098	0.155	0.185	0.093	0.24	0.26	0.10	0.22	0.25	0.086	0.135	0.160	0.086	0.21	0.23	0.081	0.29	0.30	
630	0.068	0.094	0.25	0.27	0.081	0.155	0.175	0.076	0.24	0.25	0.08	0.22	0.24	0.072	0.135	0.150	0.072	0.21	0.22	0.066	0.28	0.29	
800	0.053		-		0.068	0.150	0.165	0.061	0.24	0.25		-		0.060	0.130	0.145	0.060	0.21	0.22	0.053	0.28	0.29	
1000	-0.042		-		0.059	0.150	0.160	0.050	0.24	0.24		-		0.052	0.130	0.140	0.052	0.20	0.21	0.044	0.28	0.28	

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.















CENELEC



