


6381Y Flexible Cable - Single Core BS6004, PVC - 6mm² to 400mm²



Description

Flexible, single core, PVC telecoms cable. For use in DC power supplies on telecoms equipment and power applications where flexible cable is a requirement.

Key Features



Voltage Rating

1.5mm² To 35mm²: 450/750V
50mm² and Above: 600/1000V



Minimum Bending Radius

Up to 50mm² - 3x overall diameter
Above 50mm² - 4 x overall diameter



Flame Retardancy

BS EN 60332-1-2



Temperature Limits

Flexed: -15°C to +70°C

Core Colours

Standard colours available:



Red available in 25mm only

Standards

- 50mm² and above: BS EN/IEC 60502-1
- BS EN/IEC 60228
- Up to 35mm²: Generally to BS 6004,
- BS EN/IEC 60332-1-2

Construction

- **Conductor:** Class 5 flexible, stranded copper
- **Insulation:** PVC (Poly Vinyl Chloride)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** All sizes available in Blue, Grey, Green/Yellow

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

6381Y Flexible Cable - Single Core BS6004, PVC - 6mm² to 400mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Size
6381Y6	6	1	84/0.3	7.7	105	20/16
6381Y10	10	1	80/0.40	8.8	151	20S
6381Y16	16	1	126/0.40	9.9	208	20S
6381Y25	25	1	196/0.40	11.4	303	20
6381Y35	35	1	276/0.40	12.7	401	20
6381Y50	50	1	396/0.40	14.6	560	25
6381Y70	70	1	360/0.50	16.1	748	25
6381Y95	95	1	475/0.50	18.6	990	25
6381Y120	120	1	608/0.50	20.2	1233	32
6381Y150	150	1	756/0.50	22.5	1528	32
6381Y185	185	1	925/0.50	25.1	1857	32
6381Y240	240	1	1221/0.50	28.3	2419	40
6381Y300	300	1	1525/0.50	31.2	3032	40
6381Y400	400	1	2013/0.50	35.4	3937	50S



TABLE 4D1A

Conductor cross-sectional area	CURRENT-CARRYING CAPACITY (amperes):						Ambient temperature: 30 °C				
							Conductor operating temperature: 70 °C				
	Reference Method A (enclosed in conduit in thermally insulating wall etc)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method F (in free air or on a perforated cable tray horizontal or vertical)				
						Touching		Spaced by one diameter			
2 cables, single-phase AC or DC		3 or 4 cables, three-phase AC		2 cables, single-phase AC or DC flat and touching		2 cables, single-phase AC or DC flat		2 cables, single-phase AC or DC 3 cables three-phase AC flat			
								Horizontal			
								Vertical			
I (mm ²)	2 (A)	3 (A)	4 (A)	5 (A)	6 (A)	7 (A)	8 (A)	9 (A)	10 (A)	11 (A)	12 (A)
1	11	10.5	13.5	12	15.5	14	-	-	-	-	-
1.5	14.5	13.5	17.5	15.5	20	18	-	-	-	-	-
2.5	20	18	24	21	27	25					
4	26	24	32	28	37	33					
6	34	31	41	36	47	43					
10	46	42	57	50	65	59					
16	61	56	76	68	87	79					
25	80	73	101	89	114	104	131	114	110	146	130
35	99	89	125	110	141	129	162	143	137	181	162
50	119	108	151	134	182	167	196	174	167	219	197
70	151	136	192	171	234	214	251	225	216	281	254
95	182	164	232	207	284	261	304	275	264	341	311
120	210	188	269	239	330	303	352	321	308	396	362
150	240	216	300	262	381	349	406	372	356	456	419
185	273	245	341	296	436	400	463	427	409	521	480
240	321	286	400	346	515	472	546	507	485	615	569
300	367	328	458	394	594	545	629	587	561	709	659
400	-	-	546	467	694	634	754	689	656	852	795
500	-	-	626	533	792	723	868	789	749	982	920
630	-	-	720	611	904	826	1005	905	855	1138	1070
800	-	-	-	-	1030	943	1086	1020	971	1265	1188
1000	-	-	-	-	1154	1058	1216	1149	1079	1420	1337



TABLE 4D1B

VOLTAGE DROP (per ampere per metre):

Conductor operating temperature: 70 °C

Conductor cross-sectional area	2 cables DC	2 cables, single-phase AC						3 or 4 cables, three-phase AC														
		Reference Methods A & B (enclosed in conduit or trunking)			Reference Methods C & F (clipped direct, on tray or in free air)			Reference Methods A & B (enclosed in conduit or trunking)		Reference Methods C & F (clipped direct, on tray or in free air)												
					Cables touching		Cables spaced*			Cables touching, Trefoil		Cables touching, Flat		Cables spaced*, Flat								
1	2	3	4	5	6	7	8	9														
mm ²	(mV/Nm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)	(mV/Afm)						
1	44	44	44	44	38	38	38	38														
1.5	29	29	29	29	25	25	25	25														
2.5	18	18	18	18	15	15	15	15														
4	11	11	11	11	9.5	9.5	9.5	9.5														
6	7.3	7.3	7.3	7.3	6.4	6.4	6.4	6.4														
10	4.4	4.4	4.4	4.4	3.8	3.8	3.8	3.8														
16	2.8	2.8	2.8	2.8	2.4	2.4	2.4	2.4														
		r	X	Z	r	X	Z	r	X	Z	r	X	Z	r	X	Z	r	X	Z			
25	1.75	1.80	0.33	1.80	1.75	0.20	1.75	0.29	1.80	1.50	0.29	1.55	1.50	0.175	1.50	1.50	0.25	1.55	1.50	0.32	1.55	
35	1.25	1.30	0.31	1.30	1.25	0.195	1.25	0.28	1.30	1.10	0.27	1.10	1.10	0.170	1.10	1.10	0.24	1.10	1.10	0.32	1.15	
50	0.93	0.95	0.30	1.00	0.93	0.190	0.95	0.93	0.97	0.81	0.26	0.85	0.80	0.165	0.82	0.80	0.24	0.84	0.80	0.32	0.86	
70	0.63	0.65	0.29	0.72	0.63	0.185	0.66	0.63	0.27	0.69	0.56	0.25	0.61	0.55	0.160	0.57	0.55	0.24	0.60	0.55	0.31	0.63
95	0.46	0.49	0.28	0.56	0.47	0.180	0.50	0.47	0.27	0.54	0.42	0.24	0.48	0.41	0.155	0.43	0.41	0.23	0.47	0.40	0.31	0.51
120	0.36	0.39	0.27	0.47	0.37	0.175	0.41	0.37	0.26	0.45	0.33	0.23	0.41	0.32	0.150	0.36	0.32	0.23	0.40	0.32	0.30	0.44
150	0.29	0.31	0.27	0.41	0.30	0.175	0.34	0.29	0.26	0.39	0.27	0.23	0.36	0.26	0.150	0.30	0.26	0.23	0.34	0.26	0.30	0.40
185	0.23	0.25	0.27	0.37	0.24	0.170	0.29	0.24	0.26	0.35	0.22	0.23	0.32	0.21	0.145	0.26	0.21	0.22	0.31	0.21	0.30	0.36
240	0.180	0.195	0.26	0.33	0.185	0.165	0.25	0.185	0.25	0.31	0.17	0.23	0.29	0.160	0.145	0.22	0.160	0.22	0.27	0.160	0.29	0.34
300	0.145	0.160	0.26	0.31	0.150	0.165	0.22	0.150	0.25	0.29	0.14	0.23	0.27	0.130	0.140	0.190	0.130	0.22	0.25	0.130	0.29	0.32
400	0.105	0.130	0.26	0.29	0.120	0.160	0.20	0.115	0.25	0.27	0.12	0.22	0.25	0.105	0.140	0.175	0.105	0.21	0.24	0.100	0.29	0.31
500	0.086	0.110	0.26	0.28	0.098	0.155	0.185	0.093	0.24	0.26	0.10	0.22	0.25	0.086	0.135	0.160	0.086	0.21	0.23	0.081	0.29	0.30
630	0.068	0.094	0.25	0.27	0.081	0.155	0.175	0.076	0.24	0.25	0.08	0.22	0.24	0.072	0.135	0.150	0.072	0.21	0.22	0.066	0.28	0.29
800	0.053	-	-	-	0.068	0.150	0.165	0.061	0.24	0.25	-	-	-	0.060	0.130	0.145	0.060	0.21	0.22	0.053	0.28	0.29
1000	-0.042	-	-	-	0.059	0.150	0.160	0.050	0.24	0.24	-	-	-	0.052	0.130	0.140	0.052	0.20	0.21	0.044	0.28	0.28

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

