

BS6346/87 Armoured Traffic Signal Cable - 1mm² to 1.5mm²



Description

Armoured PVC traffic signal cable, used to connect traffic signal equipment or in other applications that require high core configurations with tough mechanical robustness.

Key Features



Voltage Rating 600/1000 Volts



Minimum Bending Radius 10 x Overall Diameter



Flame Retardancy BS EN/IEC 60332-1-2



Temperature Limits Temperature Range: -15°C to + 70°C

Core Colours



Standards

- BS6346/87
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228

Construction

- Conductor: Class 1 solid copper
- Insulation: Polyvinyl Chloride (PVC)
- Bedding: Polyvinyl Chloride (PVC)
- Armour: Steel Wire Armour (SWA)
- Outer Sheath: Polyvinyl Chloride (PVC)
- Sheath Colour: Orange

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while $reducing\ carbon\ emissions\ in\ collaboration\ with\ our\ customers\ and\ suppliers.$



Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis



















BS6346/87 Armoured Traffic Signal Cable - 1mm² to 1.5mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Size
TRAF4X1	1	4	1/1.13	13	325	205
TRAF8X1ESWA	1	8	1/1.13	16.3	533	20
STCTRAF8X1	1	8	1/1.13	3	413	205
STCTRAF12X1E	1	12	1/1.13	15.5	785	25
STCTRAF12X1R250	1	12	1/1.13	15.6	567	20
STCTRAF16X1	1	16	1/1.13	17.9	774	20
STCTRAF20X1R250	1	20	1/1.13	19.9	905	25
TRAF4X1/5	1.5	4	1/1.38	12.5	363	20\$
STCTRAF8X1/5	1.5	8	1/1.38	15.8	534	20
STCTRAF12X1/5R250	1.5	12	1/1.38	18.5	704	20
STCTRAF16X1/5R250	1.5	16	1/1.38	20	836	20
STCTRAF20X1/5R250	1.5	20	1/1.38	21.5	1040	25
STCTRAF27X1/5SWA R250	1.5	27	1/1.38	23.75	1280	25

















CENELEC



TRAFFIC CABLE - ELECTRICAL PROPERTIES

CABLE TYPE	NOMINAL CROSS SECTIONAL AREA mm²	NUMBER OF CORES	MAXIMUM CONDUCTOR RESISTANCE AT 20°C	CURRENT CARRYING CAPACITY		
				IN AIR	DIRECT BURIAL	VOLTAGE DROP
			Ω/ΚΜ	(AMPS)	(AMPS)	MV/A/M
BS6346 PVC TRAFFIC CABLE	1	8	18.10	12.00	10.50	38
BS6346 PVC TRAFFIC CABLE	1	12	18.10	10.00	8.70	38
BS6346 PVC TRAFFIC CABLE	1	16	18.10	9.00	8.00	38
BS6346 PVC TRAFFIC CABLE	1	20	18.10	8.00	7.10	38
BS6346 PVC TRAFFIC CABLE	1.5	8	12.10	15.00	13.50	25
BS6346 PVC TRAFFIC CABLE	1.5	12	12.10	13.00	11.70	25
BS6346 PVC TRAFFIC CABLE	1.5	16	12.10	11.00	10.00	25
BS6346 PVC TRAFFIC CABLE	1.5	20	12.10	10.00	9.10	25
LOOP FEEDER CABLE	1.5	2	12.10	10.00	9.00	38
LOOP FEEDER CABLE	1.5	4	12.10	11.00	10.00	38
LOOP FEEDER CABLE	2.5	2	13.42	31.00	26.00	27
LOOP FEEDER CABLE	2.5	4	13.42	28.00	23.00	27
LOOP DETECTOR CABLE	1.5	1	12:10	14.50	20.00	29
LOOP DETECTOR CABLE	2.5	1	18.10	20.00	27.00	18

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

