


## Bare Copper Cable Hard Drawn - BS7884 - 50mm<sup>2</sup> to 70mm<sup>2</sup>



### Description

Non-insulated, non-sheathed, flexible stranded bare hard drawn copper cable used in earthing electrical systems, overhead line systems and power distribution networks.

### Key Features



**Voltage Rating**  
450 Volts

### Standards

- Hard drawn copper: BS7884
- IEC 60228

### Construction

- **Conductor:** Stranded plain annealed compacted circular copper conductor non insulated and non sheathed

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Bare Copper Cable Hard Drawn - BS7884 - 50mm<sup>2</sup> to 70mm<sup>2</sup> - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)
HDC050/19	50	1	19/1.80	9.2	405
HDC050/7	50	1	7/3.0	9.2	445
HDC070/19	70	1	19/2.1	10.65	640
HDC070/7	70	1	7/3.55	10.65	621

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.