

Câble de protection cathodique monoconducteur HMWPE - PVDF, non armé - 6 mm² à 95 mm²



Description

The single core armoured cable is designed for use in cathodic protection groundbeds where the evolution of chlorine gas is expected. PVDF has excellent resistance to chemical attack. HMWPE Cable is available from 6mm² - 95mm².

Fonctionnalités clés



Tension nominale
600/1000 volts



Rayon de courbure minimal
10 x diamètre total



Limites de température
Plage de température : -55 °C à +105 °C

Normes

- IEC 60502
- BS EN/IEC 60228

Construction

- **Conducteur:** Cuivre toronné de classe 2
- **Isolation:** Polyfluorure de vinylidène (PVDF)
- **Gaine:** Polyéthylène à haut poids moléculaire (HMWPE)

Laboratoire d'assurance qualité

Laboratoire d'essai et de formation Cleveland Cable

Notre centre d'essai de câbles à la pointe de la technologie garantit que chaque câble répond aux normes de qualité et de conformité les plus strictes grâce à des essais continus et rigoureux. Le cas échéant, les câbles sont testés et certifiés de manière indépendante par BASEC afin de garantir leur conformité totale.



CPR

Cleveland Cable Company s'engage à respecter le règlement sur les produits de construction (CPR). Le cas échéant, tous les câbles fabriqués après le 1er juillet 2017 ont été évalués conformément aux exigences du CPR, avec une documentation complète à l'appui.



Notre engagement en faveur du développement durable

Nous nous engageons à atteindre la neutralité carbone en tant que partenaire commercial, employeur et membre de la communauté.

En pensant et en agissant de manière durable, nous offrons un excellent service à la clientèle tout en réduisant les émissions de carbone en collaboration avec nos clients et nos fournisseurs.



ecovadis

Cleveland Cable Company a été évaluée de manière indépendante par EcoVadis, un fournisseur mondialement reconnu de notations de durabilité des entreprises. Notre score nous place parmi les 35 % des meilleures entreprises évaluées dans le monde, ce qui reflète notre engagement fort en matière de performance environnementale, sociale et éthique.

ecovadis

Câble de protection cathodique monoconducteur HMWPE - PVDF, non armé - 6 mm² à 95 mm² - Dimensions

Référence	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)
HMWPE1X6	6	1	7/1.03	7.2	92
HMWPE1X10	10	1	7/1.34	8.1	138
HMWPE1X16	16	1	7/1.69	9.3	200
HMWPE1X25	25	1	7/2.10	10.4	288
HMWPE1X35	35	1	19/1.51	11.6	385
HMWPE1X50	50	1	19/1.75	13	500
HMWPE1X70	70	1	19/2.12	14.7	715
HMWPE1X95	95	1	19/2.50	16.5	958

TABLE 4E1A

CURRENT-CARRYING CAPACITY (amperes)

Ambient temperature: 30°C
 Conductor operating temperature:90°C

Conductor cross sectional area	Reference Method A (enclosed in conduit in thermally insulating wall etc.)		Reference Method B (enclosed in conduit on a wall or in trunking etc.)		Reference Method C (clipped direct)		Reference Method F (in free air or on a perforated cable tray etc horizontal or vertical etc) Touching			Reference Method G (in free air) Spaced by one cable diameter		
	2 cables single phase AC or DC	3 or 4 cables, three-phase AC	2 cables single phase AC or DC	3 or 4 cables, three phase AC	2 cables single phase AC or DC flat and touching	3 or 4 cables, three phase AC flat and touching or trefoil	2 cables single phase AC or DC flat	3 cables, three phase AC flat	3 cables, three phase AC trefoil	2 cables, single-phase AC or DC or 3 cables three-phase AC flat		
	A	A	A	A	A	A	A	A	A	Horizontal	Vertical	
mm ²	A	A	A	A	A	A	A	A	A	A	A	A
1	14	13	17	15	19	17.5	-	-	-	-	-	-
1.5	19	17	23	20	25	23	-	-	-	-	-	-
4	35	31	42	37	46	41	-	-	-	-	-	-
6	45	40	54	48	59	54	-	-	-	-	-	-
10	61	54	75	66	81	74	-	-	-	-	-	-
16	81	73	100	88	109	99	-	-	-	-	-	-
25	106	95	133	117	143	130	161	141	135	182	161	
35	131	117	164	144	176	161	200	176	169	226	201	
50	158	141	198	175	228	209	242	216	207	275	246	
70	200	179	253	222	293	268	310	279	268	353	318	
95	241	216	306	269	355	326	377	342	328	430	389	
120	278	249	354	312	413	379	437	400	383	500	454	
150	318	285	393	342	476	436	504	464	444	577	527	
185	362	324	449	384	545	500	575	533	510	661	605	
240	424	380	528	450	644	590	679	634	607	781	719	
300	486	435	603	514	743	681	783	736	703	902	833	
400	-	-	683	584	868	793	940	868	823	1085	1008	
500	-	-	783	666	990	904	1083	998	946	1253	1169	
630	-	-	900	764	1130	1033	1254	1151	1088	1454	1362	
800	-	-	-	-	1288	1179	1358	1275	1214	1581	1485	
1000	-	-	-	-	1443	1323	1520	1436	1349	1775	1671	

Where it is intended to connect the cables in this table to equipment or accessories designed to operate at a temperature lower than the maximum operating temperature of the cable, the cables should be rated at the maximum operating temperature of the equipment or accessory (see Regulation 512.1.5). Where it is intended to group a cable in this table with other cables, the cable should be rated at the lowest of the maximum operating temperatures of any of the cables in the group (see Regulation 12.1.5). For cables having flexible conductors see section 2.4 of this appendix for adjustment factors for current-carrying capacity and voltage drop.



TABLE 4E1B

VOLTAGE DROP (per ampere per metre)

Conductor operating temperature:90°C

Conductor cross sectional area (mm ²)	2 cables, DC (mV/ A/m)	2 cables, single-phase AC									3 or 4 cables, three-phase AC											
		Reference Methods A & B (enclosed in conduit or trunking)			Reference Methods C, F & G (clipped direct, on tray or in free air)						Reference Methods A & B (enclosed in conduit or trunking)			Reference Methods C, F & G (clipped direct, on tray or in free air)								
					Cables touching			Cables spaced*						Cables touching, Trefoil			Cables touching, Flat			Cables spaced* Flat		
		(mV/A/m)			(mV/A/m)			(mV/A/m)			(mV/A/m)			(mV/A/m)			(mV/A/m)			(mV/A/m)		
1	46	46			46			46			40			40			40			40		
1.5	31	31			31			31			27			27			27			27		
2.5	19	19			19			19			16			16			16			16		
4	12	12			12			12			10			10			10			10		
6	7.9	7.9			7.9			7.9			6.8			6.8			6.8			6.8		
10	4.7	4.7			4.7			4.7			4.0			4.0			4.0			4.0		
16	2.9	2.9			2.9			2.9			2.5			2.5			2.5			2.5		
		R	X	Z	R	X	Z	R	X	Z	R	X	Z	R	X	Z	R	X	Z	R	X	Z
25	1.850	1.850	0.310	1.900	1.850	0.190	1.850	1.850	0.280	1.850	1.600	0.270	1.650	1.600	0.165	1.600	1.600	0.190	1.600	1.600	0.270	1.650
35	1.350	1.350	0.290	1.350	1.350	0.180	1.350	1.350	0.270	1.350	1.150	0.250	1.150	1.150	0.155	1.150	1.150	0.180	1.150	1.150	0.260	1.200
50	0.990	1.000	0.290	1.050	0.990	0.180	1.000	0.990	0.270	1.000	0.870	0.250	0.900	0.860	0.155	0.870	0.860	0.180	0.870	0.860	0.260	0.890
70	0.680	0.700	0.280	0.750	0.680	0.175	0.710	0.680	0.260	0.730	0.600	0.240	0.650	0.590	0.150	0.610	0.590	0.175	0.620	0.590	0.250	0.650
95	0.490	0.510	0.270	0.580	0.490	0.170	0.520	0.490	0.260	0.560	0.440	0.230	0.500	0.430	0.145	0.450	0.430	0.170	0.460	0.430	0.250	0.490
120	0.390	0.410	0.260	0.480	0.390	0.165	0.430	0.390	0.250	0.470	0.350	0.230	0.420	0.340	0.140	0.370	0.340	0.165	0.380	0.340	0.240	0.420
150	0.320	0.330	0.260	0.430	0.320	0.165	0.360	0.320	0.250	0.410	0.290	0.230	0.370	0.280	0.140	0.310	0.280	0.165	0.320	0.280	0.240	0.370
185	0.250	0.270	0.260	0.370	0.260	0.165	0.300	0.250	0.250	0.360	0.230	0.230	0.320	0.220	0.140	0.260	0.220	0.165	0.280	0.220	0.240	0.330
240	0.190	0.210	0.260	0.330	0.200	0.160	0.250	0.195	0.250	0.310	0.185	0.220	0.290	0.170	0.140	0.220	0.170	0.165	0.240	0.170	0.240	0.290
300	0.155	0.175	0.250	0.310	0.160	0.160	0.220	0.155	0.250	0.290	0.150	0.220	0.270	0.140	0.140	0.195	0.135	0.160	0.210	0.135	0.240	0.270
400	0.120	0.140	0.250	0.290	0.130	0.155	0.200	0.125	0.240	0.270	0.125	0.220	0.250	0.110	0.135	0.175	0.110	0.160	0.195	0.110	0.240	0.260
500	0.093	0.120	0.250	0.280	0.105	0.155	0.185	0.098	0.240	0.260	0.100	0.220	0.240	0.090	0.135	0.160	0.088	0.160	0.180	0.085	0.240	0.250
630	0.072	0.100	0.250	0.270	0.086	0.155	0.175	0.078	0.240	0.250	0.088	0.210	0.230	0.074	0.135	0.150	0.071	0.160	0.170	0.068	0.230	0.240
800	0.056	-	-	-	0.072	0.150	0.170	0.064	0.240	0.250	-	-	-	0.062	0.130	0.145	0.059	0.155	0.165	0.055	0.230	0.240
1000	0.045	-	-	-	0.063	0.150	0.165	0.054	0.240	0.240	-	-	-	0.055	0.130	0.140	0.050	0.155	0.165	0.047	0.230	0.240

NOTE: * Spacings larger than one cable diameter will result in a larger voltage drop.

LES INFORMATIONS CONTENUES DANS CETTE FICHE TECHNIQUE SONT FOURNIES À TITRE INDICATIF UNIQUEMENT ET SONT SUSCEPTIBLES D'ÊTRE MODIFIÉES SANS PRÉAVIS NI RESPONSABILITÉ. NOUS ESTIMONS QUE CES INFORMATIONS SONT CORRECTES AU MOMENT DE LEUR PUBLICATION. VEUILLEZ NOTER QUE LORS DU CHOIX DES ACCESSOIRES POUR CÂBLES, LES DIMENSIONS RÉELLES DES CÂBLES PEUVENT VARIER EN RAISON DES TOLÉRANCES DE FABRICATION.