# NHXMH-J Domestic & Industrial Cable - BS EN60332-3-24, LSZH - 1.5mm<sup>2</sup> to 10mm<sup>2</sup>



#### **Description**

LZSH wiring cable, indoor and outdoor use, suitable for industrial or domestic applications and designed for dry, moist or wet areas i.e. under plaster and in concrete. Not suitable for exposure to direct sunlight.

#### **Key Features**



Voltage Rating 300/500Volts



Minimum Bending Radius Fixed: 4 x overall diameter




Flame Retardancy BS EN/IEC 60332-1-2 BS EN/IEC 60332-3-24



Temperature Limits
Temperature Range: -5°C to +90°C

#### **Core Colours**



#### Standards

- IEC/EN 60754-1/2
- IEC 60332-1
- BS EN/IEC 61034-2
- BS EN/IEC 60228
- BS EN/IEC 60332-3-24
- Generally to VDE 0250-214

#### Construction

- Conductor: Class 1 solid copper
- Insulation: Cross Linked polyethylene (XLPE)
- Filler: Extruded Thermoplastic
- Outer Sheath: Low Smoke Zero Halogen (LSZH)
- Sheath Colour: Grey

### **QA Lab**

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

## ecovadis



















## NHXMH-J Domestic & Industrial Cable - BS EN60332-3-24, LSZH - 1.5mm² to 10mm² - Dimensions

Reference	Conductor Size (mm2)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)
NHXMHJ3X1/5	1.5	3	1/1.38	9.9	120
NHXMHJ4X1/5	1.5	4	1/1.38	10.7	140
NHXMHJ5X1/5	1.5	5	1/1.38	11.5	170
NHXMHJ7X1/5	1.5	7	1/1.38	12.6	210
NHXMHJ12X1/5	1.5	12	1/1.38	16.8	415
NHXMHJ3X2/5	2.5	3	1/1.78	11.4	165
NHXMHJ4X2/5	2.5	4	1/1.78	12.3	200
NHXMHJ5X2/5	2.5	5	1/1.78	13.3	245
NHXMHJ3X4R	4	3	1/2.25	13	240
NHXMHJ5X4R	4	5	1/2.25	16	370
NHXMHJ3X6R	6	3	1/2.76	14.7	330
NHXMHJ5X6R	6	5	1/2.76	17.5	406
NHXMHJ3X10	10	3	1/3.56	17.7	510
NHXMHJ5X10	10	5	1/3.56	21.3	770



















For cables having flexible conductors, see section 2.4 of this Appendix in regulations for adjustment factors for current-carrying capacity and voltage drop

## **TABLE 4D2A**

CURRENT-CARRYING CAPACITY (amperes):

Ambient temperature: 30 °C Conductor operating temperature: 70 °C

Conductor	Reference Method A (enclosed in conduit in thermally insulating wall etc)		Reference Method B (enclosed in conduit on a wall or in trunking etc)		Reference Method C (clipped direct)		Reference Method E (in free air or on a perforated cable tray etc, horizontal or vertical)	
cross- sectional area	1 two-core cable*, single phase AC or DC	1 three- core cable* or 1 four-core cable, three phase AC	1 two-core cable*, single-phase AC or DC	1 three- core cable* or 1 four-core cable, three phase AC	1 two-core cable*, single phase AC or DC	1 three- core cable* or 1 four-core cable, three phase AC	1 two-core cable*, single phase AC or DC	1 three- core cable* or 1 four-core cable, three phase AC
I	2	3	4	5	6	7	8	9
(mm2)	(A)	(A)	(A)	(A)	(A)	(A)	(A)	(A)
1	11	10	13	11.5	15	13.5	17	14.5
1.5	14	13	16.5	15	19.5	17.5	22	18.5
2.5	18.5	17.5	23	20	27	24	30	25
4	25	23	30	27	36	32	40	34
6	32	29	38	34	46	41	51	43
10	43	39	52	46	63	57	70	60
16	57	52	69	62	85	76	94	80
25	75	68	90	80	112	96	119	101
35	92	83	111	99	138	119	148	126
50	110	99	133	118	168	144	180	153
70	139	125	168	149	213	184	232	196
95	167	150	201	179	258	223	282	238
120	192	172	232	206	299	259	328	276
150	219	196	258	225	344	299	379	319
185	248	223	294	255	392	341	434	364
240	291	261	344	297	461	403	514	430
300	334	298	394	339	530	464	593	497
400			470	402	634	557	715	597

<sup>\*</sup> with or without a protective conductor















CENELEC





VOLTAGE DROP (per ampere per metre):

Conductor operating temperature: 70°C

Conductor cross-sectional area	Two-core cable, DC	Two-core cable, single-phase AC		Three- or four-core cable, three-phase AC			
1	2	3		4			
(mm2)	(mV/A/m)		(mV/A/m)		(mV/A/m)		
1	44		44		38		
1.5	29		29		25		
2.5	18	18			15		
4	11	11			9.5		
6	7.3	7.3			6.4		
10	4.4	4.4			3.8		
16	2.8	2.8		2.4			
		r	×	z	r	Х	z
25	1.75	1.75	0.170	1.75	1.50	0.145	1.50
35	1.25	1.25	0.165	1.25	1.10	0.145	1.10
50	0.93	0.93	0.165	0.94	0.80	0.140	0.81
70	0.63	0.63	0.160	0.65	0.55	0.140	0.57
95	0.46	0.47	0.155	0.50	0.41	0.135	0.43
120	0.36	0.38	0.155	0.41	0.33	0.135	0.35
150	0.29	0.30	0.155	0.34	0.26	0.130	0.29
185	0.23	0.25	0.150	0.29	0.21	0.130	0.25
240	0.180	0.190	0.150	0.24	0.165	0.130	0.21
300	0.145	0.155	0.145	0.21	0.135	0.130	0.185
400	0.105	0.115	0.145	0.185	0.100	0.125	0.160

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

