

## NYYJ Mains & Control Cable Non-Armoured, PVC - 1.5mm<sup>2</sup> to 16mm<sup>2</sup>



### Description

Unarmoured power and control cable is most suited for energy supply in fixed installations. NYY Cable can be installed indoors where there is little chance of mechanical damage. Cables can be fixed on cable trays, within conduits or fixed to walls. This cable is not suitable for direct burial.

### Key Features



**Voltage Rating**  
600/1000 Volts



**Minimum Bending Radius**  
12 x Overall Diameter



**Flame Retardancy**  
BS EN 60332-1-2



**Temperature Limits**  
Fixed: -15°C to +70°C

### Core Colours

2 core - Brown Blue

3 core - Brown Blue Green Yellow

4 core - Brown Blue Black Green Yellow

5 core - Brown Blue Black Grey Green Yellow

### Standards

- Generally to VDE 0276-603
- BS EN/IEC 60228
- BS EN/IEC 60332-1-2
- IEC 60502-1

### Construction

- Conductor:** Up to 6mm<sup>2</sup> Class 1 solid copper conductor Above 10mm<sup>2</sup> Class 2 stranded copper
- Insulation:** Polyvinyl Chloride (PVC)
- Filler:** Polyvinyl Chloride (PVC)
- Outer Sheath:** Polyvinyl Chloride (PVC)

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

**ecovadis**

## NYYJ Mains & Control Cable Non-Armoured, PVC - 1.5mm<sup>2</sup> to 16mm<sup>2</sup> - Dimensions

Reference	Conductor Size (mm <sup>2</sup> )	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
NYY2X1/5	1.5	2	1/1.38	10.5	157	0.5	20S
NYY3X1/5	1.5	3	1/1.38	11	190	0.5	20
NYY4X1/5	1.5	4	1/1.38	11.8	220	0.5	20
NYY5X1/5	1.5	5	1/1.38	12.8	270	0.6	20
NYY7X1/5	1.5	7	1/1.38	13.7	299	0.6	25
NYY2X2/5	2.5	2	1/1.78	11.3	193	0.5	20
NYY3X2/5	2.5	3	1/1.78	11.9	240	0.5	20
NYY4X2/5	2.5	4	1/1.78	12.8	290	0.6	20
NYY5X2/5	2.5	5	1/1.78	13.9	350	0.6	25
NYY7X2/5	2.5	7	1/1.78	14.9	388	0.6	25
NYY2X4	4	2	1/2.25	13	267	0.6	20
NYY3X4	4	3	1/2.25	13.7	330	0.6	25
NYY4X4	4	4	1/2.25	14.8	400	0.6	25
NYY5X4	4	5	1/2.25	16.3	480	0.7	25
NYY2X6	6	2	1/2.76	14	329	0.6	25
NYY3X6	6	3	1/2.76	14.8	420	0.6	25
NYY4X6	6	4	1/2.76	16	510	0.7	25
NYY5X6	6	5	1/2.76	17.6	600	0.7	25
NYY2X10	10	2	7/1.35	16.6	498	0.7	25
NYY3X10	10	3	7/1.35	17.8	580	0.8	25
NYY4X10	10	4	7/1.35	19.3	751	0.8	32
NYY5X10	10	5	7/1.35	21.2	910	0.9	32
NYY2X16	16	2	7/1.70	18.8	684	0.8	25
NYY3X16	16	3	7/1.70	20.2	800	0.9	32
NYY4X16	16	4	7/1.70	22	1057	0.9	32
NYY5X16	16	5	7/1.70	24.2	1257	1	32



## GENERAL CONDUCTOR PROPERTIES

NOMINAL CROSS SECTION AREA MM <sup>2</sup>	MAX RESISTANCE (Ω/Km) OF CLASS 1 SOLID CONDUCTOR AT 20 0C	MINIMUM NUMBER OF WIRES IN CLASS 2 CONDUCTOR						MAX RESISTANCE (Ω/Km) OF CLASS 2 COPPER CONDUCTOR AT 20 0C	MAX RESISTANCE(Ω/Km) OF CLASS 2 ALUMINIUM CONDUCTOR AT 20 0C		
		CIRCULAR		COMPACTED CIRCULAR		SECTOR SHAPED					
		Cu	Al	Cu	Al	Cu	Al				
1.5	12.1	7		6				12.1	-		
2.5	7.41	7	-	6	-	-	-	7.41	-		
4	4.61	7	-	6	-	-	-	4.61	-		
6	3.08	7	-	6	-	-	-	3.08	-		
10	1.83	7	7	6	6	-	-	1.83	3.08		
16	1.15	7	7	6	6	-	-	1.15	1.91		
25	0.727	7	7	6	6	6	6	0.727	1.2		
35	0.524	7	7	6	6	6	6	0.524	0.868		
50	0.387	19	19	6	6	6	6	0.387	0.641		
70	0.268	19	19	12	12	12	12	0.268	0.443		
95	0.193	19	19	15	15	15	15	0.193	0.32		
120	0.153	37	37	18	15	18	15	0.153	0.253		
150	0.124	37	37	18	15	18	15	0.124	0.206		
185	0.101	37	37	30	30	30	30	0.0991	0.164		
240	0.0775	37	37	34	30	34	30	0.0754	0.125		
300	0.062	61	61	34	30	34	30	0.0601	0.1		

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

