


PAS5308 Part1, Type2 Instrumentation Cable, Overall Screened - 0.5mm² to 2.5mm²



Description

Manufactured to PAS5308, instrumentation cables are intrinsically safe and designed for use in communication and instrumentation applications in and around process industries for transmission of signals in control systems. The signals can be analogue or digital from a variety of sensors and transducers.

For Part 1 cables: Refer to Part 1 in PAS5308 pair identification colour chart

Key Features



Voltage Rating
300/500 Volts



Minimum Bending Radius
Fixed: 12 x overall diameter



Flame Retardancy
BS EN/IEC 60332-1
BS EN/IEC 60332-3-24



Temperature Limits
Fixed: -40°C to +70°C

Core Colours

[PAS5308 pair identification colour chart](#)

Standards

- PAS5308 / BS5308
- BS EN/IEC 60332-1-2
- BS EN/IEC 60228
- BS EN/IEC 60332-3-24

Construction

- **Conductor:** Under 1mm² Class 5 flexible copper conductor
1mm² & above Class 2 stranded copper conductor
- **Insulation:** Polyethylene (PE) Laid up to form pairs
- **Screen:** Collective Aluminium/mylar tape with 0.5mm drain wire
- **Bedding:** Polyethylene (PE)
- **Armour:** Galvanised Steel Wire Armour (SWA)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Blue or Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

PAS5308 Part1,Type2 Instrumentation Cable, Overall Screened - 0.5mm² to 2.5mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Pairs	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Nylon Cleat Size	Gland Size
7125B	0.5	1 Triple	16/0.20	11	259	0.5	20/16
7118B	0.5	1	16/0.20	10.8	242	0.5	20/16
7119BU	0.5	2	16/0.20	11.7	288	0.5	20S
7119BK	0.5	2	16/0.20	11.7	11.7288	0.5	20S
7120B	0.5	5	16/0.20	17.3	535	0.7	20
7121B	0.5	10	16/0.20	22.3	868	0.9	25
7122B	0.5	20	16/0.20	28.5	1466	1.2	32
7123B	0.5	30	16/0.20	33.3	1944	1.4	32
7124B	0.5	50	16/0.20	41.5	3360	1.8	50S
7162B	0.75	1 Triple	24/0.2	11.4	288	0.5	20S
7155B	0.75	1	24/0.2	11.1	270	0.5	20/16
7156B	0.75	2	24/0.2	12.3	330	0.5	20S
7157B	0.75	5	24/0.2	19.2	719	0.8	20
7158B	0.75	10	24/0.2	24.7	1150	1.0	25
7159B	0.75	20	24/0.2	30.7	1704	1.2	32
7160B	0.75	30	24/0.2	36.9	2570	1.6	40
7161B	0.75	50	24/0.2	46.4	4400	2.0	50S
7196B	1.5	1 Triple	7/0.53	12.6	357	0.5	20S
7189B	1.5	1	7/0.53	12.3	312	0.5	20S
7190BU	1.5	2	7/0.53	13.7	397	0.6	20S
7190BK	1.5	2	7/0.53	13.7	397	30.6	20S
7191B	1.5	5	7/0.53	21.5	918	0.9	25
7192BU	1.5	10	17/0.53	27.8	1466	1.1	32
7192BK	1.5	10	7/0.53	27.8	1466	1.1	32
7193B	1.5	20	7/0.53	35.1	2519	1.4	40
7194B	1.5	30	7/0.53	41.9	3352	1.8	50S
7195B	1.5	50	7/0.53	53.4	5310	TC9	63S
7213B	2.5	1 Triple	7/0.67	13.7	407	0.6	20S
7208B	2.5	1	7/0.67	13.1	395	0.6	20S
7209B	2.5	2	7/0.67	15.9	490	0.6	20
7210B	2.5	5	7/0.67	26.5	1430	1.1	20
7211B	2.5	10	7/0.67	35.1	2235	1.4	40
7212B	2.5	20	7/0.67	46.7	3935	2.0	50

PART 1 PAIR COLOURS

PAIR	A	B
1	Black	Blue
2	Black	Green
3	Blue	Green
4	Black	Brown
5	Blue	Brown
6	Green	Brown
7	Black	White
8	Blue	White
9	Green	White
10	Brown	White
11	Black	Red
12	Blue	Red
13	Green	Red
14	Brown	Red
15	White	Red
16	Black	Orange
17	Blue	Orange
18	Green	Orange
19	Brown	Orange
20	White	Orange
21	Red	Orange
22	Black	Yellow
23	Blue	Yellow
24	Green	Yellow
25	Brown	Yellow

PAIR	A	B
26	White	Yellow
27	Red	Yellow
28	Orange	Yellow
29	Black	Grey
30	Blue	Grey
31	Green	Grey
32	Brown	Grey
33	White	Grey
34	Red	Grey
35	Orange	Grey
36	Yellow	Grey
37	Black	Violet
38	Blue	Violet
39	Green	Violet
40	Brown	Violet
41	White	Violet
42	Red	Violet
43	Orange	Violet
44	Yellow	Violet
45	Grey	Violet
46	Black	Turquoise
47	Blue	Turquoise
48	Green	Turquoise
49	Brown	Turquoise
50	White	Turquoise

For individual screened pairs, identification will be Black/Blue numbered pairs.

Two pair collectively screened cables are in quad formation colour coded in rotation, Black, Blue, Green, Brown.

Single triple will be Blue , Black, Green

PART 1 ELECTRICAL CHARACTERISTICS

NOMINAL CROSS SECTIONAL AREA (MM ²)	MUTUAL CAPACITANCE pF/m			MINIMUM INSULATION RESISTANCE AT 20°C	MAXIMUM L/R RATIO
	Cables with Collective Screen Only	1 Pair, 2 Pairs, 1 Triple Collectively Screened	Cables with Individually Screened Pairs	mohms/km	µH/ohms
0.5	75	115	115	>5	25
0.75	75	115	115	>5	25
1	75	115	115	>5	25
1.5	85	120	120	>5	40

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.