

XAI Marine Power Cable

XAI Marine Power Cable

Description Overview

Used as fixed installation cables in various electromechanical and electronic equipments of marine vehicles, in most areas & open deck in ships.
Due to its' overall screen the electromagnetic interference is minimized.

Key Features



Voltage Rating
600/1000 Volts

Core Colours

2 core -	Brown	Blue			
3 core -	Brown	Grey	Black		
4 core -	Brown	Black	Grey	Blue	
5 core -	Brown	Black	Grey	Blue	Black

Standards

Construction

- **Conductor:** Electrolytic stranded annealed copper wire Class 5. (Class 2 and / or tinned on request)
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Sheath:** Halogen-free, flame retardant, polyolefin based compound (SHF1)NOFI, With Seperating Foil

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

XAI Marine Power Cable - Dimensions

Reference	size
XAI3X16	16
XAI3X10	10
XAI3X6	6
XAI3X4	4
XAI3X2/5	2.5
XAI3X1/5	1.5

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.