

Airfield Lighting - XLPE, CTS, PVC - 6mm²



Description

Airfield lighting cables specifically designed for safety-critical airport and airfield systems, illuminating runways during aircraft take-off and the landing approach. Available in a range of materials with different screen options.

Key Features



Voltage Rating
5kV



Minimum Bending Radius
9X Overall Diameter



Temperature Limits
Temperature Range: -25°C to +90°C

Standards

- Generally to FAA L-824C
- BS EN/IEC 60228

Construction

- **Conductor:** Class 2 stranded copper
- **Insulation:** Cross Linked polyethylene (XLPE)
- **Screen:** Copper Tape Screen (CTS)
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



Airfield Lighting - XLPE, CTS, PVC - 6mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Overall Diameter(mm)
5KVXLPE1X6BKCTS	6	1	12.1

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.