Belden Equivalent 8723 SWA LSZH



Description

2 pair plus drain cable which is equivalent to Belden 8273 cable. Collectively foil screened multi pair cables for interference free high speed data transmission in digital communications systems, Audio, Control & Instrument Cable. LSZH bedding and outer sheath for indoor use and public buildings where there may be risk of fire. Steel wire armour for additional strength and robustness.

Key Features

Voltage Rating
300 Volts

Minimum Bending Radius
15 x Overall Diameter

Temperature Limits
Installation temperature: -15°C To +80°C

Core Colours

Pair 1: Black | Red

Pair 2: White | Green

Drain: Tinned Copper

Standards

- BS EN 60332-1-2
- BS EN 61034-2
- BS EN 60754-1&2
- ISO 4892-3
- LVD (2014/35/EU)

Construction

- **Conductor**: Stranded tinned copper
- **Insulation**: Polypropylene (PP)
- **Insulation Screen**: Alu/Polyester Tape (AL/PET) Screen On Each Pair
- **Drain Wire**: Tinned Copper
- **Bedding**: Low Smoke Zero Halogen (LSZH)
- **Armour**: Galvanised Steel Wire Armour (SWA)
- **Outer Sheath**: Low Smoke Zero Halogen (LSZH)
- **Sheath Colour**: Black

Training & Testing Lab

AN ISO/IEC 17025 ACCREDITED FACILITY

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing.

ISO/IEC 17025 Accredited Testing Laboratory
31196

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

CLEVELAND CABLE COMPANY

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Belden Equivalent 8723 SWA LSZH - Dimensions

Reference	AWG Stranding	No Of Conductors	No Of Pairs	Overall Diameter(mm)	Weight(Kg/Km)
CD8723SWALSF	AWG 22 (7x30)	4 Plus Drain Wire	2	10.2	210

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.