

Belden Equivalent 8760



Description

Single pair plus drain wire which is equivalent to Belden 8760. Foil screened twisted pair cables for interference free high speed data transmission in digital communications systems sound, audio and computer equipment. Suitable for outdoor installation in a duct.

Key Features



Voltage Rating
300 Volts



Minimum Bending Radius
10 x Overall Diameter



Temperature Limits
Operating temperature: -20°C To +60°C

Core Colours

Pair 1: Black Clear

Drain: Tinned Copper

Standards

- BS EN 60332-1-2
- UL1581
- BS EN 61034-2
- CPR Rated to ECA
- BS EN 60754-1&2

Construction

- **Conductor:** Stranded tinned copper
- **Insulation:** Polyethylene (PE)
- **Insulation Screen:** Aluminium/Polyester Tape Screen (AL/PET)
- **Drain Wire:** Tinned Copper
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Grey

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis

Belden Equivalent 8760 - Dimensions

| Reference | AWG Stranding | No Of Conductors | No Of Pairs | Overall Diameter(mm) | Weight(Kg/Km) |
|-----------|----------------|-------------------|-------------|----------------------|---------------|
| CD8760 | AWG 18 (16x30) | 2 Plus Drain Wire | 1 | 5.65 | 69 |

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.