

## Belden Equiv 9519



### Description

An overall foil screened cable used for data control circuits, computers and RS 232 applications.

### Key Features



**Voltage Rating**  
300 Volts



**Minimum Bending Radius**  
10 x Overall Diameter



**Temperature Limits**  
Operating temperature: -30°C to +80°C

### Core Colours

Pair 1: Black Red Pair 11: Red Yellow

Pair 2: Black White Pair 12: Red Brown

Pair 3: Black Green Pair 13: Red Orange

Pair 4: Black Blue Pair 14: Green White

Pair 5: Black Yellow Pair 15: Green Blue

Pair 6: Black Brown Pair 16: Green Yellow

Pair 7: Black Orange Pair 17: Green Brown

Pair 8: Red White Pair 18: Green Orange

Pair 9: Red Green Pair 19: White Blue

Pair 10: Red Blue

### Standards

### Construction

- **Conductor:** Stranded tinned copper
- **Insulation:** Polyvinyl Chloride (PVC)
- **Insulation Screen:** Aluminium/Polyester Tape Screen (AL/PET)
- **Drain Wire:** Tinned Copper
- **Outer Sheath:** Polyvinyl Chloride (PVC)
- **Sheath Colour:** Grey

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



#### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



#### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

#### ecovadis

## Belden Equiv 9519 - Dimensions

Reference	AWG Stranding	No Of Pairs	Overall Diameter(mm)	Weight(Kg/Km)	Diameter of Strands (mm)
CD9519MULTI	AWG 24(7)	19	11.40	168	0.20

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.