Belden Equiv 9519

Description

An overall foil screened cable used for data control circuits, computers and RS 232 applications.

Key Features

Voltage Rating
300 Volts

Minimum Bending Radius
10 x Overall Diameter

Temperature Limits
Operating temperature: -30°C to +80°C

Core Colours

Pair 1:	Black	Red	Pair 11:	Red	Yellow
Pair 2:	Black	White	Pair 12:	Red	Brown
Pair 3:	Black	Green	Pair 13:	Red	Orange
Pair 4:	Black	Blue	Pair 14:	Green	White
Pair 5:	Black	Yellow	Pair 15:	Green	Blue
Pair 6:	Black	Brown	Pair 16:	Green	Yellow
Pair 7:	Black	Orange	Pair 17:	Green	Brown
Pair 8:	Red	White	Pair 18:	Green	Orange
Pair 9:	Red	Green	Pair 19:	White	Blue
Pair 10:	Red	Blue			

Standards

Construction

- **Conductor**: Stranded tinned copper
- **Insulation**: Polyvinyl Chloride (PVC)
- **Insulation Screen**: Aluminium/Polyester Tape Screen (AL/PET)
- **Drain Wire**: Tinned Copper
- **Outer Sheath**: Polyvinyl Chloride (PVC)
- **Sheath Colour**: Grey

QA Lab

Cleveland Cable Test & Training Lab
Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.

CPR
Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.

Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.

ecovadis
Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

Belden Equiv 9519 - Dimensions

Reference	AWG Stranding	No Of Pairs	Overall Diameter(mm)	Weight(Kg/Km)	Diameter of Strands (mm)
CD9519MULTI	AWG 24(7)	19	11.40	168	0.20

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.