

Enhanced Fire Alarm & Security Cable BS5839, BS7629 - 1.5mm² to 10mm²



Description

Enhanced fire alarm and security cable. Soft Skin enhanced Fire Resistant Cables for general use in fire detection, fire alarm, voice alarm, and emergency lighting circuits. Enhanced cables are designed to carry on working for 120 minutes in a fire.

The higher fire resistance this cable provides is recommended for systems in which cables might need to operate correctly during a fire for multiple phase evacuation such as tower blocks and multi storey buildings.

Note: 6mm² and 10mm² do not hold Basec, LPCB or any 3rd party accreditations

Key Features

Core Colours

- 2 core - Brown Blue
- 3 core - Brown Black Grey
- 4 core - Brown Black Grey Blue
- 7 core and above - Black with White numbers
- Outer sheath comes in a choice of: Red White

Standards

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



Enhanced Fire Alarm & Security Cable BS5839, BS7629 - 1.5mm² to 10mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Stranding(mm)	Overall Diameter(mm)	Weight(Kg/Km)	Gland Ref	1 Hole Clip Ref	Gland Size
ENH2X1/5	1.5	2	1/1.38	8	110	251	32	20
ENH3X1/5	1.5	3	1/1.38	8.4	130	251	34	20
ENH4X1/5	1.5	4	1/1.38	9.5	160	251	37	20
ENH2X2/5	2.5	2	1/1.78	9	160	252	34	20
ENH3X2/5	2.5	3	1/1.78	10.5	200	252	40	20
ENH4X2/5	2.5	4	1/1.78	11.7	250	252	43	20
ENH2X4	4	2	7/0.85	11.3	260	252	43	20
ENH3X4	4	3	7/0.85	12.1	315	254	47	25
ENH4X4	4	4	7/0.85	13.3	380	254	51	25
ENH2X6RD	6	2	7/1.04	14.0	340	25A2	51	20
ENH4X6RD	6	4	7/1.04	16.4	500	25A2	59	25
ENH2X10RD	10	2	7/1.35	16.4	510	25A2	63	25

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.