


BS7835 3 Core Armoured Mains Cable CU XLPE SWA LSZH 8.7/15kV - 50mm² to 500mm²



Description

BS7835, 3 core copper cable, 8.7/15kV, XLPE insulation, SWA, LSZH sheath, armoured cable, water blocked, industrial power networks, power stations, 50mm², 500mm²

Key Features

Core Colours

3 Core: Brown Black Grey Tape

Outer Sheath: Red or Black

Standards

Construction

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



BS7835 3 Core Armoured Mains Cable CU XLPE SWA LSZH 8.7/15kV - 50mm² to 500mm² - Dimensions

Reference	Conductor Size (mm ²)	No Of Cores	Sheath Thickness (mm)	Overall Diameter(mm)	Weight(Kg/Km)
15KVXLPE3X50	50	3	2.10	56.5	5245
15KVXLPE3X70	70	3	2.20	60.5	6250
15KVXLPE3X95	95	3	2.30	65.0	7300
15KVXLPE3X120	120	3	2.35	68.0	8250
15KVXLPE3X150	150	3	2.50	74.5	10260
15KVXLPE3X185	185	3	2.60	77.5	11500
15KVXLPE3X240	240	3	2.75	83.0	13750
15KVXLPE3X300	300	3	2.85	88.0	16250
15KVXLPE3X400	400	3	3.10	95.0	19450
15KVXLPE3X500	500	3	3.25	104	23200

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.