

Cat 5E UTP PE 4 Pair External Cable



Description

A multipair high performance cable that consists of twisted pair conductors, used mainly for data transmission. Category 5E is recommended for all new installations, supports a frequency range of up to 100 MHz and is designed for transmission speeds of up to 100 MHz gigabit per second (Gigabit Ethernet).

Key Features



Minimum Bending Radius 8 x Overall Diameter



Temperature LimitsTemperature Range: -20°C to +60°C

Standards

- IEC 11801
- TIA/EIA 568

Construction

- Conductor: Class 1 solid copper
- Insulation: High Density Polyethylene (HDPE)
- Outer Sheath: Polyethylene (PE)
- Sheath Colour: Black

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.







CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

ecovadis



















CENELEC



CORE IDENTIFICATION

Pair 1: Blue Blue/White

Pair 2: Orange Orange/White

Pair 3: Green **Green/White**

Pair 4: **Brown** Brown /White

Sheath: Black

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.

















CENELEC

