

Centipede Overhead Line ATF Feeder Cable - Network Rail Certified



Description

Centipede Auto Transformer Feeder (ATF) cable was designed for the Railway industry and is used to deliver improved and upgraded power supplies in comparison to legacy overhead line equipment (OHL)

Centipede ATF is an along track overhead conductor cable to distribute power across the line via the autotransformers and can be used both for aerial and insulated cable routes. Centipede ATF cable is manufactured in accordance with drawing number 148/752/998.

Key Features



Core Identification
Centipede: 415-AL 1



Minimum Bending Radius
9X Overall Diameter



Temperature Limits
Temperature Range: -30°C to +70°C



Drawing Number
Centipede: 148/752

Standards

- BS EN 50182
- BS 215-1
- PADS REF: 0091/030481

Construction

- **Conductor:** Stranded Aluminium Conductors

QA Lab

Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance



Centipede Overhead Line ATF Feeder Cable - Network Rail Certified - Dimensions

Reference	Max Overall Dia	Weight(Kg/Km)
0091/03048/BARE1X400	26.46	1145

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.