

## CMP Glands BWLSF



### Description

CMP brass indoor and outdoor glands are most commonly used with Steel Wire Armoured cable (SWA). Each cable gland provides mechanical cable retention and electrical continuity via armour wire termination.

All CMP LSF cable glands are designed and tested for compliance with EN 50267-2-1, the test on gases evolved during combustion of materials applied to cables under fire conditions.

All LSF cable glands meets the requirements of London Underground LTD Fire Safety Regulations.

The brass grade for all glands is CuZn39Pb3 (CW614N) to EN12168

### Key Features

### Standards

### Construction

### QA Lab

#### Cleveland Cable Test & Training Lab

Our state-of-the-art cable testing facility ensures that every cable meets the highest standards of quality and compliance through continuous, rigorous testing. Where applicable, cables are independently tested and certified by BASEC to ensure full compliance.



### CPR

Cleveland Cable Company is committed to compliance with the Construction Products Regulation (CPR). Where applicable, all cables manufactured after 1st July 2017 have been assessed in accordance with CPR requirements, with full supporting documentation available.



### Our Sustainability Commitment

We are committed to the journey to Net Zero as a business partner, an employer and a community member.

By thinking and acting sustainably, we deliver excellent customer service while reducing carbon emissions in collaboration with our customers and suppliers.



### ecovadis

Cleveland Cable Company has been independently assessed by EcoVadis, a globally recognised provider of business sustainability ratings. Our score places us among the top 35% of companies evaluated worldwide, reflecting our strong commitment to environmental, social, and ethical performance

### ecovadis

## CMP Glands BWLSF - Dimensions

Reference
CMP

THE INFORMATION CONTAINED WITHIN THIS DATASHEET IS FOR GUIDANCE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE OR LIABILITY. WE BELIEVE THE INFORMATION IS CORRECT AT THE TIME OF PUBLICATION. PLEASE NOTE WHEN SELECTING CABLE ACCESSORIES THAT ACTUAL CABLE DIMENSIONS MAY VARY DUE TO MANUFACTURING TOLERANCES.